

Products → Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

General Information

Extended Product Type:	NF71E-13
Product ID:	1SBH137001R1371
EAN:	3471523100435
Catalog Description:	NF71E-13 100-250V50/60HZ-DC Contactor Relay
Long Description:	NF contactor relays are used for switching auxiliary and control circuits. NF contactor relays include an electronic coil interface accepting a wide control voltage U_c min. ... U_c max. Only four coils cover control voltages between 24...500 V 50/60 Hz or 20...500 V DC. NF contactor relays can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any coil change. NF contactor relays have built-in surge protection and do not require additional surge suppressors. - Poles: 8-pole contactor relays with a non-removable front-mounted auxiliary contact block (mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1 and including the "Mechanically Linked" symbol on the contactor relay side) - Control Circuit: AC or DC operated - Accessories: a wide range of Accessories is available.

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

Popular Downloads

Data Sheet, Technical Information:	1SBC101433D0201
Instructions and Manuals:	1SBC101027M6801

Dimensions

Product Net Width:	45 mm
Product Net Depth:	110.5 mm
Product Net Height:	86 mm
Product Net Weight:	0.320 kg

Technical

Number of Auxiliary Contacts NO:	7
Number of Auxiliary Contacts NC:	1
Standards:	IEC 60947-5-1 and EN 60947-5-1, UL 508, CSA C22.2 N°14
Rated Operational Voltage:	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Frequency (f):	Auxiliary Circuit 50 / 60 Hz

Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-5-1, $q = 40 \text{ }^\circ\text{C}$ 16 A
Rated Operational Current AC-15 (I_e):	(220 / 240 V) 4 A (24 / 127 V) 6 A (400 / 440 V) 3 A (500 V) 2 A (690 V) 2 A
Rated Short-time Withstand Current (I_{cw}):	for 0.1 s 140 A for 1 s 100 A
Maximum Electrical Switching Frequency:	AC-15 1200 cycles per hour DC-13 900 cycles per hour
Rated Operational Current DC-13 (I_e):	(110 V) 0.55 A / 60 A (125 V) 0.55 A / 69 A (220 V) 0.27 A / 60 A (24 V) 6 A / 144 A (250 V) 0.27 A / 68 A (400 V) 0.15 A / 60 A (48 V) 2.8 A / 134 A (500 V) 0.13 A / 65 A (600 V) 0.1 A / 60 A (72 V) 1 A / 72 A
Rated Insulation Voltage (U_i):	acc. to UL/CSA 600 V acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V
Rated Impulse Withstand Voltage (U_{imp}):	6 kV
Maximum Mechanical Switching Frequency:	6000 cycles per hour
Rated Control Circuit Voltage (U_c):	50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V
Operate Time:	Between Coil De-energization and NC Contact Closing 13 ... 98 ms Between Coil De-energization and NO Contact Opening 11 ... 95 ms Between Coil Energization and NC Contact Opening 38 ... 90 ms Between Coil Energization and NO Contact Closing 40 ... 95 ms
Connecting Capacity Auxiliary Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 1 ... 2.5 mm ²
Connecting Capacity Control Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 1 ... 2.5 mm ²
Wire Stripping Length:	Auxiliary Circuit 10 mm Control Circuit 10 mm
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20

Terminal Type: Screw Terminals

Environmental

Ambient Air Temperature: Close to Contactor for Storage -60 ... +80 °C
Near Contactor for Operation in Free Air -40 ... +70 °C

Climatic Withstand: Category B according to IEC 60947-1 Annex Q

**Maximum Operating Altitude
Permissible:** 3000 m

**Resistance to Vibrations acc. to
IEC 60068-2-6:** 5 ... 300 Hz 4 g closed position / 2 g open position

**Resistance to Shock acc. to IEC
60068-2-27:** Closed, Shock Direction: B1 25 g
Open, Shock Direction: B1 5 g
Shock Direction: A 30 g
Shock Direction: B2 15 g
Shock Direction: C1 25 g
Shock Direction: C2 25 g

Technical UL/CSA

Tightening Torque UL/CSA: Auxiliary Circuit 11 in·lb
Control Circuit 11 in·lb

Certificates and Declarations (Document Number)

ABS Certificate: ABS_15-GE1349500-PDA_90682247

BV Certificate: BV_2634H24899B0

CB Certificate: CB_SE-89845

CCC Certificate: CCC_2011010303465426

cUL Certificate: UL_20180227_E252354_2_1

Declaration of Conformity - CE: 1SBD250005U1000

DNV Certificate: DNV-GL_TAE00001BV

DNV GL Certificate: DNV-GL_TAE00001BV

EAC Certificate: EAC_RU C-FR ME77 B01006

Environmental Information: 1SBD250152E1000

GOST Certificate: GOST_POCCFR.ME77.B06804.pdf

Instructions and Manuals: 1SBC101027M6801

LR Certificate: LRS_C1400038

RINA Certificate: RINA_ELE084013XG

RMRS Certificate: RMRS_1300132124

RoHS Information: 1SBD251014E1000

UL Certificate: UL_20130206-E252354-2-1

UL Listing Card: UL_E252354

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	87 mm
Package Level 1 Length:	113 mm
Package Level 1 Height:	47 mm
Package Level 1 Gross Weight:	0.32 kg
Package Level 1 EAN:	3471523100435
Package Level 2 Units:	36 piece
Package Level 2 Width:	250 mm
Package Level 2 Length:	300 mm
Package Level 2 Height:	315 mm
Package Level 2 Gross Weight:	11.52 kg
Package Level 3 Units:	864 piece

Classifications

Object Classification Code:	K
ETIM 4:	EC000196 - Contactor relay
ETIM 5:	EC000196 - Contactor relay
ETIM 6:	EC000196 - Contactor relay
UNSPSC:	39121500

