

# NFZ80E-23



Products → Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

## General Information

<b>Extended Product Type:</b>	NFZ80E-23
<b>Product ID:</b>	1SBH136001R2380
<b>EAN:</b>	3471523101937
<b>Catalog Description:</b>	NFZ80E-23 100-250V50/60HZ-DC Contactor Relay
<b>Long Description:</b>	NFZ contactor relays are used for switching auxiliary and control circuits. NFZ contactor relays include an electronic coil interface accepting a wide control voltage $U_c \text{ min.} \dots U_c \text{ max.}$ Only four coils cover control voltages between 24...250 V 50/60 Hz or 12...250 V DC. NFZ contactor relays can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any coil change NFZ contactor relays allow direct control by PLC-output $\geq 24 \text{ V DC } 500 \text{ mA}$ and obtain a reduced holding coil consumption. NFZ contactor relays withstand short voltage dips and voltage sags (SEMI F47-0706 compliance) between 24...250 V 50/60 Hz NFZ contactor relays have built-in surge protection and do not require additional surge suppressors - Poles: 8-pole contactor relays - Control Circuit: AC or DC operated - Accessories: a wide range of Accessories is available.

## Ordering

<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85364900

## Popular Downloads

<b>Data Sheet, Technical Information:</b>	1SBC101434D0201
<b>Instructions and Manuals:</b>	1SBC101027M6801

## Dimensions

<b>Product Net Width:</b>	45 mm
<b>Product Net Depth:</b>	110.5 mm
<b>Product Net Height:</b>	86 mm
<b>Product Net Weight:</b>	0.360 kg

## Technical

<b>Number of Auxiliary Contacts NO:</b>	8
<b>Number of Auxiliary Contacts NC:</b>	0
<b>Standards:</b>	IEC 60947-5-1 and EN 60947-5-1, UL 508, CSA C22.2 N°14
<b>Rated Operational Voltage:</b>	Auxiliary Circuit 690 V Main Circuit 690 V

<b>Rated Frequency (f):</b>	Auxiliary Circuit 50 / 60 Hz
<b>Conventional Free-air Thermal Current (<math>I_{th}</math>):</b>	acc. to IEC 60947-5-1, $\varrho = 40\text{ °C}$ 16 A
<b>Rated Operational Current AC-15 (<math>I_e</math>):</b>	(220 / 240 V) 4 A (24 / 127 V) 6 A (400 / 440 V) 3 A (500 V) 2 A (690 V) 2 A
<b>Rated Short-time Withstand Current (<math>I_{cw}</math>):</b>	for 0.1 s 140 A for 1 s 100 A
<b>Maximum Electrical Switching Frequency:</b>	AC-15 1200 cycles per hour DC-13 900 cycles per hour
<b>Rated Operational Current DC-13 (<math>I_e</math>):</b>	(110 V) 0.55 A / 60 A (125 V) 0.55 A / 69 A (220 V) 0.27 A / 60 A (24 V) 6 A / 144 A (250 V) 0.27 A / 68 A (400 V) 0.15 A / 60 A (48 V) 2.8 A / 134 A (500 V) 0.13 A / 65 A (600 V) 0.1 A / 60 A (72 V) 1 A / 72 A
<b>Rated Insulation Voltage (<math>U_i</math>):</b>	acc. to UL/CSA 600 V acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V
<b>Rated Impulse Withstand Voltage (<math>U_{imp}</math>):</b>	6 kV
<b>Maximum Mechanical Switching Frequency:</b>	6000 cycles per hour
<b>Rated Control Circuit Voltage (<math>U_c</math>):</b>	50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V
<b>Operate Time:</b>	Between Coil De-energization and NC Contact Closing 13 ... 98 ms Between Coil De-energization and NO Contact Opening 11 ... 95 ms Between Coil Energization and NC Contact Opening 38 ... 90 ms Between Coil Energization and NO Contact Closing 40 ... 95 ms
<b>Connecting Capacity Auxiliary Circuit:</b>	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup> Rigid 1/2x 1 ... 2.5 mm <sup>2</sup>
<b>Connecting Capacity Control Circuit:</b>	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup> Rigid 1/2x 1 ... 2.5 mm <sup>2</sup>
<b>Wire Stripping Length:</b>	Auxiliary Circuit 10 mm Control Circuit 10 mm

**Degree of Protection:** acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20  
acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20

**Terminal Type:** Screw Terminals

## Environmental

**Ambient Air Temperature:** Close to Contactor for Storage -60 ... +80 °C  
Near Contactor for Operation in Free Air -40 ... +70 °C

**Climatic Withstand:** Category B according to IEC 60947-1 Annex Q

**Maximum Operating Altitude  
Permissible:** 3000 m

**Resistance to Vibrations acc. to  
IEC 60068-2-6:** 5 ... 300 Hz 4 g closed position / 2 g open position

**Resistance to Shock acc. to IEC  
60068-2-27:** Closed, Shock Direction: B1 25 g  
Open, Shock Direction: B1 5 g  
Shock Direction: A 30 g  
Shock Direction: B2 15 g  
Shock Direction: C1 25 g  
Shock Direction: C2 25 g

## Technical UL/CSA

**Tightening Torque UL/CSA:** Auxiliary Circuit 11 in·lb  
Control Circuit 11 in·lb

## Certificates and Declarations (Document Number)

**ABS Certificate:** ABS\_15-GE1349500-PDA\_90682247

**BV Certificate:** BV\_2634H24899B0

**CB Certificate:** CB\_SE-89845

**CCC Certificate:** CCC\_2011010303465426

**cUL Certificate:** UL\_20180227\_E252354\_2\_1

**Declaration of Conformity - CE:** 1SBD250005U1000

**DNV Certificate:** DNV-GL\_TAE00001BV

**DNV GL Certificate:** DNV-GL\_TAE00001BV

**EAC Certificate:** EAC\_RU C-FR ME77 B01006

**Environmental Information:** 1SBD250152E1000

**GOST Certificate:** GOST\_POCCFR.ME77.B07174.pdf

**Instructions and Manuals:** 1SBC101027M6801

**LR Certificate:** LRS\_C1400038

**RINA Certificate:** RINA\_ELE084013XG

**RMRS Certificate:** RMRS\_1300132124

**RoHS Information:** 1SBD251014E1000

**UL Certificate:** UL\_20130206-E252354-2-1

## Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	87 mm
Package Level 1 Length:	113 mm
Package Level 1 Height:	47 mm
Package Level 1 Gross Weight:	0.36 kg
Package Level 1 EAN:	3471523101937
Package Level 2 Units:	36 piece
Package Level 2 Width:	250 mm
Package Level 2 Length:	300 mm
Package Level 2 Height:	315 mm
Package Level 2 Gross Weight:	12.96 kg
Package Level 3 Units:	864 piece

## Classifications

Object Classification Code:	K
ETIM 4:	EC000196 - Contactor relay
ETIM 5:	EC000196 - Contactor relay
ETIM 6:	EC000196 - Contactor relay
UNSPSC:	39121500

