

PRODUCT-DETAILS

NS40E-26

NS40E-26 230V50/60HZ Contactor Relay



General Information

| | |
|-----------------------|---|
| Extended Product Type | NS40E-26 |
| Product ID | 1SBH101001R2640 |
| EAN | 3471523002265 |
| Catalog Description | NS40E-26 230V50/60HZ Contactor Relay |
| Long Description | NS... contactor relays are used for switching auxiliary circuits and control circuits. - Poles and auxiliary contacts blocks: 4-pole contactor relays, front-mounted add-on auxiliary contact blocks (mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1) - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available. |

Classifications

| | |
|------------------------------------|----------------------------|
| Object Classification Code | K |
| ETIM 4 | EC000196 - Contactor relay |
| ETIM 5 | EC000196 - Contactor relay |
| ETIM 6 | EC000196 - Contactor relay |
| ETIM 7 | EC000196 - Contactor relay |
| UNSPSC | 39121529 |
| IDEA Granular Category Code (IGCC) | 4755 >> Contactors |

Container Information

| | |
|-----------------------|---------|
| Package Level 1 Units | 1 piece |
|-----------------------|---------|

| | |
|--------------------------------|---------------|
| Package Level 1 Width | 78 mm |
| Package Level 1 Depth / Length | 80 mm |
| Package Level 1 Height | 48 mm |
| Package Level 1 Gross Weight | 0.22 kg |
| Package Level 1 EAN | 3471523002265 |
| Package Level 2 Units | 40 piece |
| Package Level 2 Width | 250 mm |
| Package Level 2 Depth / Length | 315 mm |
| Package Level 2 Height | 195 mm |
| Package Level 2 Gross Weight | 8.8 kg |
| Package Level 3 Units | 960 piece |

Certificates and Declarations (Document Number)

| | |
|--------------------------------|--------------------------|
| CB Certificate | CB_CN_32453 |
| CCC Certificate | CCC_2007010305248106 |
| Declaration of Conformity - CE | 1SBD250016U1000 |
| Environmental Information | 1SBD250158E1000 |
| GOST Certificate | GOST_POCCNME77B07821.pdf |
| Instructions and Manuals | 1SBC101020M9701 |
| RoHS Information | 1SBD251002E1000 |
| UL Certificate | UL_220108-E312527A |
| UL Listing Card | NOA_E312527.pdf |

Technical UL/CSA

| | |
|--------------------------|--|
| Tightening Torque UL/CSA | Auxiliary Circuit 9 in-lb Control Circuit 9 in-lb |
|--------------------------|--|

Environmental

| | |
|--|---|
| Ambient Air Temperature | Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air -40 ... +70 °C |
| Climatic Withstand | Category B according to IEC 60947-1 Annex Q |
| Maximum Operating Altitude Permissible | 3000 m |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5 ... 300 Hz 3 g Closed position / 2 g Open position |
| Resistance to Shock acc. to IEC 60068-2-27 | Closed, Shock Direction: C1 19 g Closed, Shock Direction: C2 16 g Open, Shock Direction: C1 8 g Open, Shock Direction: C2 13 g Shock Direction: A 20 g Shock Direction: B1 5 g Shock Direction: B2 15 g |
| RoHS Status | Following EU Directive 2002/95/EC August 18, 2005 and amendment |

Technical

| | |
|---------------------------------|---|
| Number of Auxiliary Contacts NO | 4 |
| Number of Auxiliary Contacts NC | 0 |

| | |
|--|--|
| Standards | IEC 60947-5-1 and EN 60947-5-1, UL 508, CSA C22.2 N°14 |
| Rated Operational Voltage | Auxiliary Circuit 690 V Main Circuit 690 V |
| Rated Frequency (f) | Auxiliary Circuit 50 / 60 Hz |
| Conventional Free-air Thermal Current (I_{th}) | acc. to IEC 60947-5-1, $q = 40\text{ °C}$ 10 A |
| Rated Operational Current AC-15 (I_e) | (220 / 240 V) 4 A (24 / 127 V) 6 A (400 / 440 V) 3 A (500 V) 2 A (690 V) 2 A |
| Rated Short-time Withstand Current (I_{cw}) | for 0.1 s 140 A for 1 s 100 A |
| Maximum Electrical Switching Frequency | AC-15 1200 cycles per hour DC-13 900 cycles per hour |
| Rated Operational Current DC-13 (I_e) | (110 V) 0.55 A / 60 W (220 V) 0.27 A / 60 W (125 V) 0.55 A / 69 W (24 V) 6 A / 144 W (250 V) 0.27 A / 68 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W |
| Rated Insulation Voltage (U_i) | acc. to UL/CSA 600 V acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V |
| Rated Impulse Withstand Voltage (U_{imp}) | 6 kV |
| Maximum Mechanical Switching Frequency | 3600 cycles per hour |
| Rated Control Circuit Voltage (U_c) | 50 Hz 230 V 60 Hz 230 V |
| Operate Time | Between Coil De-energization and NC Contact Closing 7 ... 22 ms Between Coil De-energization and NO Contact Opening 5 ... 19 ms Between Coil Energization and NC Contact Opening 6 ... 18 ms Between Coil Energization and NO Contact Closing 9 ... 24 ms |
| Connecting Capacity Auxiliary Circuit | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 0.75 ... 2.5 mm ² |
| Connecting Capacity Control Circuit | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 0.75 ... 2.5 mm ² |
| Wire Stripping Length | Auxiliary Circuit 9 mm Control Circuit 9 mm |
| Degree of Protection | acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 |
| Terminal Type | Screw Terminals |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width | 45 mm |
| Product Net Depth / Length | 72.5 mm |
| Product Net Height | 68 mm |
| Product Net Weight | 0.22 kg |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SBC100173C0201 |
| Instructions and Manuals | 1SBC101020M9701 |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85364900 |

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

