

OT315E04CL



Products → Low Voltage Products and Systems → Switches → Change-over and Transfer Switches
→ Manual Change-over Switches

General Information

| | |
|-------------------------------|--|
| Extended Product Type: | OT315E04CL |
| Product ID: | 1SCA106406R1001 |
| EAN: | 6417019402031 |
| Catalog Description: | OT315E04CL CHANGE-OVER SWITCH |
| Long Description: | OT315E04CL CHANGE-OVER SWITCH, Handle and shaft need to be ordered separately, Closed transition |

Ordering

| | |
|--------------------------------|----------|
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85365080 |

Popular Downloads

| | |
|---|-----------------|
| Data Sheet, Technical Information: | 1SCC303003C0201 |
| Instructions and Manuals: | 1SCC303008M0203 |

Dimensions

| | |
|----------------------------|----------------------|
| Product Net Width: | 265 mm |
| Product Net Height: | 185 mm |
| Product Net Depth: | 203 mm |
| Product Net Weight: | 7.055 kg 15.55 lb |

Technical

| | |
|--|---|
| Rated Operational Current AC-21A (I_e): | (380 ... 415 V) 315 A (500 V) 315 A (690 V) 315 A |
| Rated Operational Current AC-22A (I_e): | (380 ... 415 V) 315 A (500 V) 315 A (690 V) 315 A |
| Rated Operational Current AC-23A (I_e): | (380 ... 415 V) 315 A (500 V) 315 A (690 V) 315 A |
| Rated Operational Current AC-31B (I_e): | (380 ... 415 V) 315 A |
| Rated Operational Current AC-33B (I_e): | (380 ... 415 V) 315 A |

| | |
|--|--|
| Rated Operational Power AC-23A (P_e): | (380 ... 415 V) 160 kW (500 V) 220 kW (690 V) 315 kW |
| Conventional Free-air Thermal Current (I_{th}): | q = 40 °C 315 A |
| Conventional Thermal Current (I_{the}): | Fully Enclosed 315 A |
| Rated Impulse Withstand Voltage (U_{imp}): | 12 kV |
| Rated Insulation Voltage (U_i): | 1000 V |
| Rated Operational Voltage: | 1000 V |
| Rated Short-time Withstand Current (I_{cw}): | for 1 s 15 kiloampere rms |
| Power Loss: | 6.5 W |
| Pollution Degree: | 3 |
| Handle Type: | Handle and shaft not included |
| Fourth Pole Position: | Right Side |
| Fourth Pole Type: | Switched - Simultaneous Function |
| Switches Operating Mechanism: | Mechanism at the End of the Switch 04 (Left Side) |
| Distance Between Phases: | Standard |
| Position of Line Terminals: | Top In - Bottom Out, Bottom In - Top Out |
| Operating Mode: | Front operated |
| Mounting Type: | Base mounting |
| Number of Poles: | 4 |

Environmental

Environmental Information: 1SCC303050D0201

Certificates and Declarations (Document Number)

Declaration of Conformity - CE: 1SCC303046D2702

Environmental Information: 1SCC303050D0201

Instructions and Manuals: 1SCC303008M0203

Container Information

Package Level 1 Units: 1 piece

Package Level 1 Width: 240 mm

Package Level 1 Length: 325 mm

Package Level 1 Height: 218 mm

Package Level 1 Gross Weight: 7.505 kg
16.55 lb

Package Level 1 EAN:

6417019402031

Classifications

Object Classification Code: Q

ETIM 5: EC000216 - Switch disconnecter

ETIM 6: EC000216 - Switch disconnecter

