

OTM200E3YM230C



Products → Low Voltage Products and Systems → Switches → Change-over and Transfer Switches
→ Motorized bypass switches

General Information

Extended Product Type:	OTM200E3YM230C
Product ID:	1SCA141437R1001
EAN:	6417019690186
Catalog Description:	OTM200E3YM230C MOTORIZED BYPASS SWITCH
Long Description:	OTM200E3YM230C MOTORIZED BYPASS SWITCH, Direct mounted handle, Open transition

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Popular Downloads

Data Sheet, Technical Information:	1SCC303003C0201
Instructions and Manuals:	1SCC301080M0003

Dimensions

Product Net Width:	296 mm
Product Net Height:	150 mm
Product Net Depth:	236 mm
Product Net Weight:	296 kg

Technical

Rated Operational Current AC-21A (I _e):	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
---	---

Rated Operational Current AC-22A (I _e):	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
---	---

Rated Operational Current AC-23A (I _e):	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
---	---

Rated Operational Power AC-23A (P _e):	(380 ... 415 V) 110 kW (500 V) 132 kW (690 V) 200 kW
---	--

Conventional Free-air Thermal Current (I_{th}):	q = 40 °C 200 A
--	-----------------

Motor Operational Voltage:	220 ... 240 V AC
-----------------------------------	------------------

Handle Type:	Direct mounted handle
Switches Operating Mechanism:	Mechanism at the End of the Switch
Distance Between Phases:	Standard
Position of Line Terminals:	Top In - Bottom Out, Bottom In - Top Out
Operating Mode:	Front operated
Standards:	IEC 60947-3
Mounting Type:	Base mounting
Number of Poles:	3

Certificates and Declarations (Document Number)

Instructions and Manuals: 1SCC301080M0003

Container Information

Package Level 1 EAN: 6417019690186

