

PRODUCT-DETAILS

# OTM200E4YM230C

## OTM200E4YM230C MOTORIZED BYPASS SWITCH



### General Information

Extended Product Type	OTM200E4YM230C
Product ID	1SCA141438R1001
EAN	6417019690193
Catalog Description	OTM200E4YM230C MOTORIZED BYPASS SWITCH
Long Description	OTM200E4YM230C MOTORIZED BYPASS SWITCH, Direct mounted handle, Open transition

### Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301080M0003

### Dimensions

Product Net Width	331 mm
Product Net Height	150 mm
Product Net Depth / Length	236 mm
Product Net Weight	331 kg

### Technical

Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 110 kW (500 V) 132 kW (690 V) 200 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	q = 40 °C 200 A
Motor Operational Voltage	220 ... 240 V AC
Handle Type	Direct mounted handle
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism at the End of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	4

---

### Certificates and Declarations (Document Number)

---

Instructions and Manuals	1SCC301080M0003
--------------------------	-----------------

---



---

### Container Information

---

Package Level 1 EAN	6417019690193
---------------------	---------------

---



---

### Classifications

---

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

---



---

### Categories

---

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Motorized bypass switches

