OTM400E3YM230C



Products + Low Voltage Products and Systems + Switches + Change-over and Transfer Switches Motorized bypass switches

General Information

Extended Product Type: OTM400E3YM230C **Product ID:** 1SCA136735R1001 EAN: 6417019652603

Catalog Description: OTM400E3YM230C MOTORIZED BYPASS SWITCH

OTM400E3YM230C MOTORIZED BYPASS SWITCH, Direct mounted hand Long Description:

le, Open transition

Ordering

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85365080

Popular Downloads

Data Sheet, Technical Information: 1SCC303003C0201

Instructions and Manuals: 1SCC301080M0003

Dimensions

Product Net Width: 342 mm

Product Net Height: 185 mm

Product Net Depth: 285 mm

Product Net Weight: 12.2 kg

Technical

Rated Operational Current AC-21A

(380 ... 415 V) 400 A

(l_e):

(500 V) 400 A (690 V) 400 A

Rated Operational Current AC-22A

(l_e):

(380 ... 415 V) 400 A (500 V) 400 A

(690 V) 400 A

Rated Operational Current AC-23A

(380 ... 415 V) 400 A (500 V) 400 A

(690 V) 400 A

Rated Operational Power AC-23A

(P_e):

(l_e):

(380 ... 415 V) 220 kW

(500 V) 280 kW

(690 V) 400 kW

Conventional Free-air Thermal

Current (Ith):

q = 40 °C 400 A

220 ... 240 V AC **Motor Operational Voltage:**

Handle Type:	Direct mounted handle
Switches Operating Mechanism:	Mechanism at the End of the Switch
Distance Between Phases:	Standard
Position of Line Terminals:	Top In - Bottom Out, Bottom In - Top Out
Operating Mode:	Front operated
Standards:	IEC 60947-3
Mounting Type:	Base mounting
Number of Poles:	3

Certificates and Declarations (Document Number)

Instructions and Manuals: 1SCC301080M0003

Container Information

Package Level 1 EAN: 6417019652603

