OTM800E3YM230C



Products + Low Voltage Products and Systems + Switches + Change-over and Transfer Switches + Motorized bypass switches

General Information

 Extended Product Type:
 OTM800E3YM230C

 Product ID:
 1SCA136616R1001

 EAN:
 6417019651460

Catalog Description: OTM800E3YM230C MOTORIZED BYPASS SWITCH

Long Description: OTM800E3YM230C MOTORIZED BYPASS SWITCH, Direct mounted hand

le, Open transition

Ordering

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85365080

Popular Downloads

Data Sheet, Technical Information: 1SCC303003C0201

Instructions and Manuals: 1SCC301080M0003

Dimensions

Product Net Width: 415 mm

Product Net Height: 250 mm

Product Net Depth: 450 mm

Product Net Weight: 415 kg

Technical

Rated Operational Current AC-21A

(380 ... 415 V) 800 A

(l_e):

(500 V) 800 A (690 V) 800 A

Rated Operational Current AC-22A

(l_e):

(380 ... 415 V) 800 A (500 V) 800 A

(690 V) 800 A

Rated Operational Current AC-23A

(l_e):

(380 ... 415 V) 800 A

(500 V) 800 A (690 V) 800 A

Rated Operational Power AC-23A

(P_e):

(380 ... 415 V) 450 kW

(500 V) 560 kW (690 V) 800 kW

Conventional Free-air Thermal

Current (Ith):

q = 40 °C 800 A

Motor Operational Voltage: 220 ... 240 V AC

Handle Type:	Direct mounted handle
Switches Operating Mechanism:	Mechanism at the End of the Switch
Distance Between Phases:	Standard
Position of Line Terminals:	Top In - Bottom Out, Bottom In - Top Out
Operating Mode:	Front operated
Standards:	IEC 60947-3
Mounting Type:	Base mounting
Number of Poles:	3

Certificates and Declarations (Document Number)

Instructions and Manuals: 1SCC301080M0003

Container Information

Package Level 1 EAN: 6417019651460

