## OTM800E4YM230C



Products + Low Voltage Products and Systems + Switches + Change-over and Transfer Switches + Motorized bypass switches

General Information	
Extended Product Type:	OTM800E4YM230C
Product ID:	1SCA136614R1001
EAN:	6417019651446
Catalog Description:	OTM800E4YM230C MOTORIZED BYPASS SWITCH
Long Description:	OTM800E4YM230C MOTORIZED BYPASS SWITCH, Direct mounted hand
	le, Open transition
Ordering	
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080
Popular Downloads	
Data Sheet, Technical Information	: 1SCC303003C0201
Instructions and Manuals:	1SCC301080M0003
Dimensions	
Product Net Width:	480 mm
Product Net Height:	250 mm
Product Net Depth:	450 mm
Product Net Weight:	480 kg
Technical	
Rated Operational Current AC-21A	(380 415 V) 800 A
(I <sub>e</sub> ):	(500 V) 800 A
	(690 V) 800 A
Rated Operational Current AC-22A	(380 415 V) 800 A
(I <sub>e</sub> ):	(500 V) 800 A
	(690 V) 800 A
Rated Operational Current AC-23A	
(I <sub>e</sub> ):	(500 V) 800 A
	(690 V) 800 A
Rated Operational Power AC-23A (P <sub>e</sub> ):	(380 415 V) 450 kW (500 V) 560 kW
(Fe).	(690 V) 800 kW
Conventional Free-air Thermal	q = 40 °C 800 A
Conventional Free-air Therman Current (I <sub>th</sub> ):	y = 40 0 000 A
Motor Operational Voltage:	220 240 V AC
motor operational voltage.	220 240 V AG

Handle Type:	Direct mounted handle
Fourth Pole Position:	Right Side
Fourth Pole Type:	Switched - Simultaneous Function
Switches Operating Mechanism:	Mechanism at the End of the Switch
Distance Between Phases:	Standard
Position of Line Terminals:	Top In - Bottom Out, Bottom In - Top Out
Operating Mode:	Front operated
Standards:	IEC 60947-3
Mounting Type:	Base mounting
Number of Poles:	4

## Certificates and Declarations (Document Number)

Instructions and Manuals: 1SCC301080M0003

## **Container Information**

Package Level 1 EAN:

6417019651446

