## OTU25B3MS2



Products + Low Voltage Products and Systems + Enclosed Switches + Enclosed Switch-Disconnectors

General Information Extended Product Type: Product ID: EAN: Catalog Description: Long Description:	OTU25B3MS2 1SCA132666R1001 6417019617718 OTU25B3MS2 Enclosed Switch Disconnector Enclosed Switch Disconnector, 3-p. 400V AC22 25A, Plastic enclosure, Bla ck Round handle.
Ordering	
Minimum Order Quantity:	4 piece
Customs Tariff Number:	85365080
Popular Downloads	
Data Sheet, Technical Information	: 1SCC342003B0201
Instructions and Manuals:	1SCC340156M0205
Dimensions	
Product Net Width:	100 mm
Product Net Height:	161 mm
Product Net Depth:	115 mm
Product Net Weight:	0.42 kg
Technical	
Rated Operational Current AC-22/ (I <sub>e</sub> ):	A (380 415 V) 25 A (690 V) 25 A
Rated Operational Current AC-23A (I <sub>e</sub> ):	A (380 415 V) 20 A (690 V) 11 A
Conventional Thermal Current (I <sub>the</sub> ):	Fully Enclosed 32 A
Rated Insulation Voltage (U <sub>i</sub> ):	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage:	Main Circuit 750 V
Rated Short-Circuit Making Capacity (I <sub>cm</sub> ):	(690 V) 0.705 kA
Rated Short-time Withstand Current (I <sub>cw</sub> ):	for 1 s 0.5 kA
Power Loss:	at Rated Operating Conditions per Pole 0.6 W
Pollution Degree:	3

Handle Color:	Black
Handle Type:	Round handle
Standards:	IEC60947-3
Number of Poles:	3
Cable Cross-Section:	27 mm²
Cable Entry Position:	Up/Down
Cable Outlets Per Side:	2xø25.5 / 2xø25.5
Degree of Protection:	acc. to IEC 60529 IP65
Enclosure Material:	Plastic
Maximum Mounted Auxiliary Contacts:	2 NO, 2 NC
Tightening Torque:	0.8 N·m
Environmental	
RoHS Status:	Following EU Directive 2011/65/EU
Kono otatus.	
Certificates and Declarations (Document Number)	
BV Certificate:	1SCC340018D0204
Declaration of Conformity - CE:	1SCC340003D2704
DNV Certificate:	1SCC340045D0203
DNV GL Certificate:	1SCC340045D0203
Instructions and Manuals:	1SCC340156M0205
Container Information	
Package Level 1 Units:	1 piece
Package Level 1 Width:	125 mm
Package Level 1 Length:	215 mm
Package Level 1 Height:	340 mm
Package Level 1 Gross Weight:	0.42 kg
Package Level 1 EAN:	6417019617718
-	
Classifications	
Object Classification Code:	Q
ETIM 5:	EC000216 - Switch disconnector
ETIM 6:	EC000216 - Switch disconnector
ETIM 7:	EC000216 - Switch disconnector

