

# OTU25BA4MS2



Products → Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch-Disconnectors

## General Information

<b>Extended Product Type:</b>	OTU25BA4MS2
<b>Product ID:</b>	1SCA132683R1001
<b>EAN:</b>	6417019617787
<b>Catalog Description:</b>	OTU25BA4MS2 Enclosed Switch Disconnecter
<b>Long Description:</b>	Enclosed Switch Disconnecter, 4-p. 400V AC22 25A, Plastic enclosure, Red Yellow Round handle.

## Ordering

<b>Minimum Order Quantity:</b>	4 piece
<b>Customs Tariff Number:</b>	85365080

## Popular Downloads

<b>Data Sheet, Technical Information:</b>	1SCC342003B0201
<b>Instructions and Manuals:</b>	1SCC340156M0205

## Dimensions

<b>Product Net Width:</b>	100 mm
<b>Product Net Height:</b>	161 mm
<b>Product Net Depth:</b>	115 mm
<b>Product Net Weight:</b>	0.42 kg

## Technical

<b>Rated Operational Current AC-22A (<math>I_e</math>):</b>	(380 ... 415 V) 25 A (690 V) 25 A
<b>Rated Operational Current AC-23A (<math>I_e</math>):</b>	(380 ... 415 V) 20 A (690 V) 11 A
<b>Conventional Thermal Current (<math>I_{the}</math>):</b>	Fully Enclosed 32 A
<b>Rated Insulation Voltage (<math>U_i</math>):</b>	acc. to IEC/EN 60664-1 750 V
<b>Rated Operational Voltage:</b>	Main Circuit 750 V
<b>Rated Short-Circuit Making Capacity (<math>I_{cm}</math>):</b>	(690 V) 0.705 kA
<b>Rated Short-time Withstand Current (<math>I_{cw}</math>):</b>	for 1 s 0.5 kA
<b>Power Loss:</b>	at Rated Operating Conditions per Pole 0.6 W
<b>Pollution Degree:</b>	3

<b>Handle Color:</b>	Red / Yellow
<b>Handle Type:</b>	Round handle
<b>Standards:</b>	IEC60947-3
<b>Number of Poles:</b>	4
<b>Cable Cross-Section:</b>	27 mm <sup>2</sup>
<b>Cable Entry Position:</b>	Up/Down
<b>Cable Outlets Per Side:</b>	2xø25.5 / 2xø25.5
<b>Degree of Protection:</b>	acc. to IEC 60529 IP65
<b>Enclosure Material:</b>	Plastic
<b>Maximum Mounted Auxiliary Contacts:</b>	2 NO, 2 NC
<b>Tightening Torque:</b>	0.8 N·m

## Environmental

**RoHS Status:** Following EU Directive 2011/65/EU

## Certificates and Declarations (Document Number)

<b>BV Certificate:</b>	1SCC340018D0204
<b>Declaration of Conformity - CE:</b>	1SCC340003D2704
<b>DNV Certificate:</b>	1SCC340045D0203
<b>DNV GL Certificate:</b>	1SCC340045D0203
<b>Instructions and Manuals:</b>	1SCC340156M0205

## Container Information

<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	125 mm
<b>Package Level 1 Length:</b>	215 mm
<b>Package Level 1 Height:</b>	340 mm
<b>Package Level 1 Gross Weight:</b>	0.42 kg
<b>Package Level 1 EAN:</b>	6417019617787

## Classifications

<b>Object Classification Code:</b>	Q
<b>ETIM 5:</b>	EC000216 - Switch disconnecter
<b>ETIM 6:</b>	EC000216 - Switch disconnecter
<b>ETIM 7:</b>	EC000216 - Switch disconnecter

