

OTU32B3MS2



Products → Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch-Disconnectors

General Information

| | |
|-------------------------------|--|
| Extended Product Type: | OTU32B3MS2 |
| Product ID: | 1SCA132667R1001 |
| EAN: | 6417019617725 |
| Catalog Description: | OTU32B3MS2 Enclosed Switch Disconnecter |
| Long Description: | Enclosed Switch Disconnecter, 3-p. 400V AC22 32A, Plastic enclosure, Black Round handle. |

Ordering

| | |
|--------------------------------|----------|
| Minimum Order Quantity: | 4 piece |
| Customs Tariff Number: | 85365080 |

Popular Downloads

| | |
|---|-----------------|
| Data Sheet, Technical Information: | 1SCC342003B0201 |
| Instructions and Manuals: | 1SCC340156M0205 |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width: | 100 mm |
| Product Net Height: | 161 mm |
| Product Net Depth: | 115 mm |
| Product Net Weight: | 0.42 kg |

Technical

| | |
|--|--|
| Rated Operational Current AC-22A (I_e): | (380 ... 415 V) 32 A (690 V) 32 A |
| Rated Operational Current AC-23A (I_e): | (380 ... 415 V) 23 A (690 V) 12 A |
| Conventional Thermal Current (I_{the}): | Fully Enclosed 40 A |
| Rated Insulation Voltage (U_i): | acc. to IEC/EN 60664-1 750 V |
| Rated Operational Voltage: | Main Circuit 750 V |
| Rated Short-Circuit Making Capacity (I_{cm}): | (690 V) 0.705 kA |
| Rated Short-time Withstand Current (I_{cw}): | for 1 s 0.5 kA |
| Power Loss: | at Rated Operating Conditions per Pole 1.6 W |
| Pollution Degree: | 3 |

| | |
|--|------------------------|
| Handle Color: | Black |
| Handle Type: | Round handle |
| Standards: | IEC60947-3 |
| Number of Poles: | 3 |
| Cable Cross-Section: | 27 mm ² |
| Cable Entry Position: | Up/Down |
| Cable Outlets Per Side: | 2xø25.5 / 2xø25.5 |
| Degree of Protection: | acc. to IEC 60529 IP65 |
| Enclosure Material: | Plastic |
| Maximum Mounted Auxiliary Contacts: | 2 NO, 2 NC |
| Tightening Torque: | 0.8 N·m |

Environmental

RoHS Status: Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

| | |
|--|-----------------|
| BV Certificate: | 1SCC340018D0204 |
| Declaration of Conformity - CE: | 1SCC340003D2704 |
| DNV Certificate: | 1SCC340045D0203 |
| DNV GL Certificate: | 1SCC340045D0203 |
| Instructions and Manuals: | 1SCC340156M0205 |

Container Information

| | |
|--------------------------------------|---------------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 125 mm |
| Package Level 1 Length: | 215 mm |
| Package Level 1 Height: | 340 mm |
| Package Level 1 Gross Weight: | 0.42 kg |
| Package Level 1 EAN: | 6417019617725 |

Classifications

| | |
|------------------------------------|--------------------------------|
| Object Classification Code: | Q |
| ETIM 5: | EC000216 - Switch disconnecter |
| ETIM 6: | EC000216 - Switch disconnecter |
| ETIM 7: | EC000216 - Switch disconnecter |

