# OTU32B4MS2



Products + Low Voltage Products and Systems + Enclosed Switches + Enclosed Switch-Disconnectors

General Information

**Extended Product Type:** OTU32B4MS2

**Product ID:** 1SCA132681R1001 EAN: 6417019617763

OTU32B4MS2 Enclosed Switch Disconnector **Catalog Description:** 

Long Description: Enclosed Switch Disconnector, 4-p. 400V AC22 32A, Plastic enclosure, Bla

ck Round handle.

Ordering

**Minimum Order Quantity:** 4 piece

**Customs Tariff Number:** 85365080

Popular Downloads

**Data Sheet, Technical Information:** 1SCC342003B0201

Instructions and Manuals: 1SCC340156M0205

**Dimensions** 

**Product Net Width:** 100 mm

**Product Net Height:** 161 mm

**Product Net Depth:** 115 mm

**Product Net Weight:** 0.42 kg

Technical

Rated Operational Current AC-22A (380 ... 415 V) 32 A

(690 V) 32 A (l<sub>e</sub>):

**Rated Operational Current AC-23A** (380 ... 415 V) 23 A

(l<sub>e</sub>): (690 V) 12 A

**Conventional Thermal Current** Fully Enclosed 40 A

(I<sub>the</sub>):

Rated Insulation Voltage (Ui): acc. to IEC/EN 60664-1 750 V

Main Circuit 750 V **Rated Operational Voltage:** 

**Rated Short-Circuit Making** 

Capacity (I<sub>cm</sub>):

for 1 s 0.5 kA

(690 V) 0.705 kA

**Rated Short-time Withstand** 

Current (Icw):

Power Loss: at Rated Operating Conditions per Pole 1.6 W

**Pollution Degree:** 3

Handle Color:	Black
Handle Type:	Round handle
Standards:	IEC60947-3
Number of Poles:	4
Cable Cross-Section:	27 mm²
Cable Entry Position:	Up/Down
Cable Outlets Per Side:	2xø25.5 / 2xø25.5
Degree of Protection:	acc. to IEC 60529 IP65
Enclosure Material:	Plastic
Maximum Mounted Auxiliary	2 NO, 2 NC
Contacts:	
Tightening Torque:	0.8 N·m

### Environmental

RoHS Status: Following EU Directive 2011/65/EU

## Certificates and Declarations (Document Number)

BV Certificate:	1SCC340018D0204
Declaration of Conformity - CE:	1SCC340003D2704
DNV Certificate:	1SCC340045D0203
DNV GL Certificate:	1SCC340045D0203
Instructions and Manuals:	1SCC340156M0205

#### **Container Information**

Package Level 1 Units:	1 piece
Package Level 1 Width:	125 mm
Package Level 1 Length:	215 mm
Package Level 1 Height:	340 mm
Package Level 1 Gross Weight:	0.42 kg
Package Level 1 EAN:	6417019617763

### Classifications

Object Classification Code:	Q
ETIM 5:	EC000216 - Switch disconnector
ETIM 6:	EC000216 - Switch disconnector
ETIM 7:	EC000216 - Switch disconnector

