OTU45BA3MS3



Products + Low Voltage Products and Systems + Enclosed Switches + Enclosed Switch-Disconnectors

General Information Extended Product Type: Product ID: EAN: Catalog Description: Long Description:	OTU45BA3MS3 1SCA132687R1001 6417019617923 OTU45BA3MS3 Enclosed Switch Disconnector Enclosed Switch Disconnector, 3-p. 400V AC22 45A, Plastic enclosure, Re
Ordering	dYellow Round handle.
C C	
Minimum Order Quantity:	2 piece
Customs Tariff Number:	85365080
Popular Downloads	
Data Sheet, Technical Information	: 1SCC342003B0201
Instructions and Manuals:	1SCC340156M0205
Dimensions	
Product Net Width:	146 mm
Product Net Height:	200 mm
Product Net Depth:	139 mm
Product Net Weight:	0.78 kg
Technical	
Rated Operational Current AC-224	A (380 415 V) 45 A
(l _e):	(690 V) 45 A
Rated Operational Current AC-234	
(l _e):	(690 V) 20 A
Conventional Thermal Current (I _{the}):	Fully Enclosed 63 A
Rated Insulation Voltage (U _i):	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage:	Main Circuit 750 V
Rated Short-Circuit Making Capacity (I _{cm}):	(690 V) 1.4 kA
Rated Short-time Withstand Current (I _{cw}):	for 1 s 1.5 kA
Power Loss:	at Rated Operating Conditions per Pole 1.5 W
Pollution Degree:	3

Handle Color:	Red / Yellow
Handle Type:	Round handle
Standards:	IEC60947-3
Number of Poles:	3
Cable Cross-Section:	42 mm²
Cable Entry Position:	Up/Down
Cable Outlets Per Side:	2xø40.5 / 2xø40.5
Degree of Protection:	acc. to IEC 60529 IP65
Enclosure Material:	Plastic
Tightening Torque:	2 N·m
Environmental	
RoHS Status:	Following EU Directive 2011/65/EU
Certificates and Declarations (Document Number)	
BV Certificate:	1SCC340018D0204
Declaration of Conformity - CE:	1SCC340003D2704
DNV Certificate:	1SCC340045D0203
DNV GL Certificate:	1SCC340045D0203
Instructions and Manuals:	1SCC340156M0205
Container Information	
Package Level 1 Units:	1 piece
Package Level 1 Width:	150 mm
Package Level 1 Length:	215 mm
Package Level 1 Height:	315 mm
Package Level 1 Gross Weight:	0.78 kg
Package Level 1 EAN:	6417019617923
Classifications	
Object Classification Code:	Q
ETIM 5:	EC000216 - Switch disconnector
ETIM 6:	EC000216 - Switch disconnector
ETIM 7:	EC000216 - Switch disconnector

