

# OVR T2 3L 40-275s P QS



Products → Low Voltage Products and Systems → Modular DIN Rail Products → Surge Protective Devices SPDs  
→ Surge Protective Devices SPD Class II

## General Information

<b>Extended Product Type:</b>	OVR T2 3L 40-275s P QS
<b>Product ID:</b>	2CTB815704R1800
<b>EAN:</b>	3660308525314
<b>Catalog Description:</b>	OVR T2 3L 40-275s P QS Surge Protective Device
<b>Long Description:</b>	B752531

## Ordering

<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85363090

## Popular Downloads

<b>Data Sheet, Technical Information:</b>	2CTC432334D0201
<b>Instructions and Manuals:</b>	2CTC432106M1701
<b>Mechanical Drawings:</b>	2CTC800015F1800.pdf 2CTC800015F1801.dxf 2CTC800015F1802.stp 2CTC800015F1803.igs

## Dimensions

<b>Product Net Width:</b>	53.4 mm
<b>Product Net Depth:</b>	76.7 mm
<b>Product Net Height:</b>	88 mm
<b>Product Net Weight:</b>	0,45 kg
<b>Width in Number of Modular Spacings:</b>	3

## Technical

<b>Type of Low Voltage Distribution System:</b>	TN-C
<b>Nominal AC Voltage of the System (U<sub>o</sub>):</b>	230 / 400 V
<b>Number of Protected Poles:</b>	3
<b>Arrester Class:</b>	II
<b>Product Main Type:</b>	T2
<b>Standards:</b>	IEC 61643-11 / EN 61643-11

<b>Product Type:</b>	QS
<b>Version:</b>	Plug-in
<b>Discharge Current:</b>	Nominal 20 kA Maximum 40 kA Total 120 kA
<b>Impulse Current:</b>	I (imp, 10 / 350 $\mu$ s) 2 kA
<b>Maximum Continuous Operating Voltage (U<sub>c</sub>):</b>	(L-PE) 275 V (L-L) 440 V (L-N) - V (N-PE) - V
<b>Voltage Rating DC:</b>	350 V
<b>Voltage Protection Level ( U<sub>p</sub>):</b>	(L-N) - V (N-PE) - V (L-PE) 1.4 V
<b>Short Circuit Withstand I<sub>cc</sub>:</b>	100 kA
<b>Temporary Overvoltage Test Value (U<sub>T</sub>):</b>	337 V
<b>Short-Circuit Protective Devices:</b>	Curve B Breakers $\leq$ 125 A Curve C Breakers $\leq$ 125 A gL Type Fuses $\leq$ 160 A gG Type Fuses $\leq$ 160 A
<b>Power Loss:</b>	49 mW
<b>Product Name:</b>	Surge Protective Device
<b>Suitable For:</b>	To protect the systems against the transient overvoltage (lightning)

## Certificates and Declarations (Document Number)

<b>Declaration:</b>	2CTC432056G1701
<b>Declaration of Conformity - CE:</b>	2CTC436004G1701
<b>Instructions and Manuals:</b>	2CTC432106M1701

## Container Information

<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	117 mm
<b>Package Level 1 Length:</b>	61 mm
<b>Package Level 1 Height:</b>	82 mm
<b>Package Level 1 Gross Weight:</b>	475 g
<b>Package Level 1 EAN:</b>	3660308525314

## Classifications

<b>Object Classification Code:</b>	141DCC
<b>ETIM 4:</b>	EC000941 - Surge protection device for power supply systems
<b>ETIM 5:</b>	EC000941 - Surge protection device for power supply systems

ETIM 6:

EC000941 - Surge protection device for power supply systems

ETIM 7:

EC000941 - Surge protection device for power supply systems

