


PRODUCT-DETAILS

# S804S-UCB40

## S804S-UCB40 High Performance MCB



### General Information

Extended Product Type	S804S-UCB40
Product ID	2CCS864001R1405
EAN	7612271203269
Catalog Description	S804S-UCB40 High Performance MCB
Long Description	S804S-UCB40 High Performance Miniature Circuit Breaker 4 Poles B Characteristic 40A 50kA 250VDC

### Technical

Standards	IEC/EN 60947-2
Number of Poles	4
Number of Protected Poles	4
Tripping Characteristic	UC-B
Rated Current ( $I_n$ )	40 A
Rated Operational Voltage	1000 V DC
Power Loss	14.8 W
Rated Insulation Voltage ( $U_i$ )	1500 V DC
Rated Short-Circuit Capacity ( $I_{cn}$ )	(400 V) 50 kA (230 V) 50 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(1000 V DC) 50 kA

Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	(750 V DC) 50 kA
Energy Limiting Class	3
Overvoltage Category	III
Pollution Degree	2
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Actuator Marking	I / O
Contact Position Indication	ON / OFF / TRIP
Degree of Protection	IP20
Connecting Capacity	Rigid 0 ... 50 mm <sup>2</sup> Flexible 0 ... 70 mm <sup>2</sup>
Built-In Depth ( $t_2$ )	82.5 mm

## Environmental

Ambient Air Temperature	Operation -25...60 °C
Environmental Conditions	Damp Heat Cyclic acc. to IEC 60068-2-30 382 + 12 cycle Damp Heat Cyclic acc. to IEC 60068-2-30 55°C @ 90-96 % Damp Heat Cyclic acc. to IEC 60068-2-30 25°C @ 90-100 % Dry Heat Test B acc. to IEC 60068-2-2 16 hours @ 55 °C Dry Heat Test B acc. to IEC 60068-2-2 2 hours @ 70 °C
RoHS Status	Following EU Directive 2011/65/EU

## Dimensions

Product Net Width	106 mm
Product Net Depth / Length	82.5 mm
Product Net Height	95 mm
Product Net Weight	980 g

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	105 mm
Package Level 1 Depth / Length	111 mm
Package Level 1 Height	99 mm
Package Level 1 Gross Weight	1010 g
Package Level 1 EAN	7612271203269

## Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85362020

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CCC413016D0601
Environmental Information	2CCY413207D0203

Instructions and Manuals	2CCC413016M0008
RoHS Information	2CCC413016D0601 9AKK107680A3903

---

## Popular Downloads

Data Sheet, Technical Information	2CCC413003C0208
Instructions and Manuals	2CCC413016M0008
Dimension Diagram	2CCC413003C0201

---

## Classifications

Object Classification Code	F
ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)

---

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs

