

# S804N-D6



Products → Low Voltage Products and Systems → Modular DIN Rail Products  
→ High Performance Circuit Breakers HPCBs

## General Information

|                               |  |
|-------------------------------|--|
| <b>Extended Product Type:</b> | S804N-D6   |
| <b>Product ID:</b>            | 2CCS894001R0061  |
| <b>EAN:</b>                   | 7612271408534  |
| <b>Catalog Description:</b>   | S804N-D6 High Performance MCB  |
| <b>Long Description:</b>      | <p>The S804N-D6 is a 4-pole High Performance Circuit breaker with D-Characteristic, with cage terminal and a rated current of 6 A. It is a current limiting device with a maximum breaking capacity of 36kA at 240/415V. It can be used for voltages up to 400/690V and in DC as well. It has two different tripping mechanisms, the thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. The S804N-D6 complies with IEC/EN 60947-2 and allows the use for industrial applications. It has numerous of approvals, therefore it can be used worldwide. The extensive range of accessory makes the use of S804N-D6 more comfortable. Due to the fast arc extinction of S804N-D6 your application will be secured.</p> |

## Ordering

|                                |          |
|--------------------------------|----------|
| <b>Minimum Order Quantity:</b> | 1 piece  |
| <b>Customs Tariff Number:</b>  | 85362020 |

## Popular Downloads

|   |                 |
|---|-----------------|
| <b>Data Sheet, Technical Information:</b> | 2CCC413003C0203 |
| <b>Instructions and Manuals:</b>          | 2CCC413016M0004 |

## Dimensions

|                            |         |
|----------------------------|---------|
| <b>Product Net Width:</b>  | 106 mm  |
| <b>Product Net Depth:</b>  | 82.5 mm |
| <b>Product Net Height:</b> | 95 mm   |
| <b>Product Net Weight:</b> | 980 g   |

## Technical

|                                       |                          |
|---------------------------------------|--------------------------|
| <b>Standards:</b>                     | IEC/EN 60947-2           |
| <b>Number of Poles:</b>               | 4                        |
| <b>Tripping Characteristic:</b>       | D                        |
| <b>Rated Current (I<sub>n</sub>):</b> | 6 A                      |
| <b>Rated Operational Voltage:</b>     | 400/690 V AC<br>375 V DC |

|   |   |
|---|---|
| <b>Power Loss:</b>  | at Rated Operating Conditions per Pole 1.8 W  |
| <b>Rated Insulation Voltage (U<sub>i</sub>):</b>                        | 690 V AC  |
| <b>Rated Frequency (f):</b>   | 50 / 60 Hz  |
| <b>Rated Ultimate Short-Circuit Breaking Capacity (I<sub>cu</sub>):</b> | (240 / 415 V AC) 36 kA<br>(254 / 440 V AC) 20 kA<br>(400 / 690 V AC) 4.5 kA<br>(500 V DC) 20 kA                               |
| <b>Rated Service Short-Circuit Breaking Capacity (I<sub>cs</sub>):</b>  | (240 / 415 V AC) 30 kA<br>(254 / 440 V AC) 15 kA<br>(400 / 690 V AC) 3 kA<br>(125 V DC) 20 kA                                 |
| <b>Overvoltage Category:</b>  | IV  |
| <b>Pollution Degree:</b>  | 3   |
| <b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>               | 8 kV  |
| <b>Housing Material:</b>  | Insulation group I, RAL 7035  |
| <b>Contact Position Indication:</b>                                     | ON / OFF / TRIP   |
| <b>Degree of Protection:</b>  | acc. to IEC 60529 IP20  |
| <b>Remarks:</b>   | Connection from top and bottom<br>Connecting with CU only<br>IP40 in enclosure with cover<br>Cage terminal with captive screw |
| <b>Electrical Endurance:</b>  | 10000 cycle   |
| <b>Mechanical Endurance (N<sub>endu</sub>):</b>                         | 10000 cycle   |
| <b>Terminal Type:</b>   | Screw Terminals   |
| <b>Connecting Capacity:</b>   | Stranded 1 ... 50 mm <sup>2</sup><br>Flexible 1 ... 70 mm <sup>2</sup>  |
| <b>Tightening Torque:</b>   | 3.5 N·m<br>31 in·lb   |
| <b>Recommended Screw Driver:</b>  | Pozidriv 2  |
| <b>Mounting on DIN Rail:</b>  | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715                |
| <b>Mounting Position:</b>   | Any   |

## Environmental

|  |   |
|--|---|
| <b>Ambient Air Temperature:</b>                        | Operation -25 ... +60 °C<br>Storage -40 ... +70 °C                          |
| <b>Resistance to Shock acc. to IEC 60068-2-27:</b>     | 5 g<br>30 ms  |
| <b>Resistance to Vibrations acc. to IEC 60068-2-6:</b> | 2 - 13.2 Hz / 1mm<br>13.2 - 100Hz / 0.7g<br>with load 100% x I <sub>e</sub> |

**Environmental Conditions:** Damp Heat Cyclic acc. to IEC 60068-2-30 12+12 cycle  
Damp Heat Cyclic acc. to IEC 60068-2-30 55°C @ 90-96%  
Damp Heat Cyclic acc. to IEC 60068-2-30 25°C @ 90-100%  
Dry Heat Test B acc. to IEC 60068-2-2 16 hour @ 55 °C  
Dry Heat Test B acc. to IEC 60068-2-2 2 hour @ 70 °C

**RoHS Status:** Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Certificates and Declarations (Document Number)

|  |                 |
|--|-----------------|
| <b>Declaration of Conformity - CE:</b> | 2CCC413016D060  |
| <b>Environmental Information:</b>      | 2CCY413207D0202 |
| <b>Instructions and Manuals:</b>       | 2CCC413016M0004 |
| <b>RoHS Information:</b>               | 2CCC413008D0206 |

## Container Information

|                                      |               |
|--------------------------------------|---------------|
| <b>Package Level 1 Units:</b>        | 1 piece       |
| <b>Package Level 1 Width:</b>        | 105 mm        |
| <b>Package Level 1 Length:</b>       | 111 mm        |
| <b>Package Level 1 Height:</b>       | 99 mm         |
| <b>Package Level 1 Gross Weight:</b> | 1010 g        |
| <b>Package Level 1 EAN:</b>          | 7612271408534 |

## Classifications

|                                    |  |
|------------------------------------|--|
| <b>Object Classification Code:</b> | F  |
| <b>ETIM 4:</b>                     | EC000042 - Miniature circuit breaker (MCB) |
| <b>ETIM 5:</b>                     | EC000042 - Miniature circuit breaker (MCB) |
| <b>ETIM 6:</b>                     | EC000042 - Miniature circuit breaker (MCB) |
| <b>ETIM 7:</b>                     | EC000042 - Miniature circuit breaker (MCB) |

