

# S1-PB1-25



Products → Low Voltage Products and Systems → Control Products → Manual Motor Starters  
→ Manual Motor Starters Accessories

## General Information

<b>Extended Product Type:</b>	S1-PB1-25
<b>Product ID:</b>	1SAM201914R1002
<b>EAN:</b>	4013614485251
<b>Catalog Description:</b>	S1-PB1-25 Power Infeed Block
<b>Long Description:</b>	S1-PB1-25 1-phase power infeed block for MS116 / MS132 / MS132-T, 25 mm <sup>2</sup> , IEC

## Ordering

<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85369010

## Popular Downloads

<b>Data Sheet, Technical Information:</b>	1SBC100192C02--
<b>Instructions and Manuals:</b>	2CDC131057M6801

## Dimensions

<b>Product Net Width:</b>	14 mm
<b>Product Net Height:</b>	34 mm
<b>Product Net Depth:</b>	24 mm
<b>Product Net Weight:</b>	0.013 kg

## Technical

<b>Terminal Type:</b>	Screw Terminals
<b>Rated Operational Voltage:</b>	690 V AC 250 V DC
<b>Rated Operational Current (I<sub>e</sub>):</b>	32 A
<b>Number of Poles:</b>	1
<b>Degree of Protection:</b>	IP20
<b>Connecting Capacity Main Circuit:</b>	Flexible 1x 4 ... 25 mm <sup>2</sup> Rigid 1x 4 ... 25 mm <sup>2</sup>
<b>Tightening Torque:</b>	Main Circuit 2 N·m
<b>Wire Stripping Length:</b>	Main Circuit 11 mm
<b>Recommended Screw Driver:</b>	M8 Pozidriv 2
<b>Standards:</b>	IEC/EN 60947-1

<b>Product Name:</b>	Power Infeed Block
<b>Suitable For:</b>	MS116 MS132 MO132 MS132-T
<b>Suitable for Product Class:</b>	Manual Motor Starter
<b>Accessory Group:</b>	Electrical
<b>Accessory Type:</b>	1-Phase Power Infeed Block

## Environmental

<b>Ambient Air Temperature:</b>	Operation -25 ... +70 °C Storage -50 ... +80 °C
<b>RoHS Status:</b>	Following EU Directive 2011/65/EU

## Technical UL/CSA

<b>Tightening Torque UL/CSA:</b>	Main Circuit 18 in·lb
----------------------------------	-----------------------

## Certificates and Declarations (Document Number)

<b>Declaration of Conformity - CE:</b>	1SAD938511-0056
<b>Instructions and Manuals:</b>	2CDC131057M6801
<b>RoHS Information:</b>	1SAD938511-0056

## Container Information

<b>Package Level 1 Width:</b>	140 mm
<b>Package Level 1 Length:</b>	15 mm
<b>Package Level 1 Height:</b>	110 mm
<b>Package Level 1 Gross Weight:</b>	0.015 kg
<b>Package Level 1 EAN:</b>	4013614485251
<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 2 Width:</b>	145 mm
<b>Package Level 2 Length:</b>	215 mm
<b>Package Level 2 Height:</b>	120 mm
<b>Package Level 2 Gross Weight:</b>	0.23 kg
<b>Package Level 2 EAN:</b>	4013614485626
<b>Package Level 2 Units:</b>	10 piece

## Classifications

<b>Object Classification Code:</b>	X
<b>ETIM 4:</b>	EC002498 - Accessories for low-voltage switch technology
<b>ETIM 5:</b>	EC000275 - Rail terminal bar
<b>ETIM 6:</b>	EC000275 - Rail terminal bar

---

**ETIM 7:** EC000275 - Rail terminal bar

---

**eClass:** 7.0 27400603

---

**UNSPSC:** 39121521

---

