

S202M-K2UC



Products → Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs

General Information

| | |
|-------------------------------|--|
| Extended Product Type: | S202M-K2UC |
| Product ID: | 2CDS272061R0277 |
| EAN: | 4013614433146 |
| Catalog Description: | Miniature Circuit Breaker - S200MUC - 2P - K - 2 ampere |
| Long Description: | The miniature circuit breaker S 200 M UC extends the established ABB System pro M compact® product range with an MCB for DC and AC applications. The S 200 M UC impresses with its performance range and the accordingly large amount of approvals. Its high inbuilt short circuit breaking capacity across the entire model line, its flexible AC and DC application and its approval and compliance in accordance with all major international and local standards make it truly unique. All current System pro M compact® accessories can be combined easily with the new model line. Whether warehousing or project engineering, planning, installing or maintaining your equipment, the S 200 M UC is a simple and flexible solution. |

Ordering

| | |
|--------------------------------|----------|
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85362010 |

Popular Downloads

| | |
|---|-----------------|
| Data Sheet, Technical Information: | 2CDC002142D0207 |
| Instructions and Manuals: | 2CDC002142D0207 |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width: | 35 mm |
| Product Net Depth: | 69 mm |
| Product Net Height: | 88 mm |
| Product Net Weight: | 0.25 kg |

Technical

| | |
|---------------------------------------|--|
| Standards: | CSA 22.2 No. 235 IEC/EN 60947-2 UL 1077 |
| Number of Poles: | 2 |
| Tripping Characteristic: | K |
| Rated Current (I_n): | 2 A |
| Rated Operational Voltage: | acc. to IEC 60947-2 440 V AC acc. to IEC 60947-2 440 V DC |

| | |
|---|--|
| Power Loss: | 3.56 W at Rated Operating Conditions per Pole 1.78 W |
| Rated Insulation Voltage (U_i): | acc. to IEC/EN 60664-1 500 V |
| Operational Voltage: | Maximum (Incl. Tolerance) 462 V AC Maximum (Incl. Tolerance) 500 V DC Minimum 12 V AC / 12 V DC |
| Rated Frequency (f): | DC 50 Hz 60 Hz |
| Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}): | (220 V DC) 25 kA (440 V AC) 10 kA (440 V DC) 10 kA |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}): | (220 V DC) 20 kA |
| Energy Limiting Class: | 3 |
| Overvoltage Category: | III |
| Pollution Degree: | 2 |
| Rated Impulse Withstand Voltage (U_{imp}): | 4 kV (6.2 kV @ sea level) kV (5.0 kV @ 2000 m) kV |
| Dielectric Test Voltage: | 50 / 60 Hz, 1 min: 2 kV |
| Housing Material: | Insulation Group I, RAL 7035 |
| Actuator Type: | Insulation group II, black, sealable |
| Contact Position Indication: | Red ON / Green OFF |
| Degree of Protection: | IP20 |
| Remarks: | IP40 in enclosure with cover; Please note polarity of device |
| Electrical Endurance: | 1500 DC cycle 20000 AC cycle |
| Mechanical Endurance (N_{endu}): | 20000 cycle |
| Terminal Type: | Screw Terminals |
| Screw Terminal Type: | Failsafe Bi-directional Cylinder-lift Terminal |
| Connecting Capacity: | Busbar 10 / 10 mm ² Flexible with Ferrule 0.75 ... 25 mm ² Flexible 0.75 ... 25 mm ² Rigid 0.75 ... 35 mm ² Stranded 0.75 ... 35 mm ² |
| Tightening Torque: | 2.8 N·m |
| Recommended Screw Driver: | Pozidriv 2 |
| Mounting on DIN Rail: | TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 |
| Mounting Position: | Any |

Environmental

| | |
|--|---|
| Ambient Air Temperature: | Operation -25 ... +55 °C Storage -40 ... +70 °C |
| Resistance to Shock acc. to IEC 60068-2-27: | 25g / 2 shocks / 13 ms |
| Resistance to Vibrations acc. to IEC 60068-2-6: | 5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In |
| Environmental Conditions: | 28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 % |

Technical UL/CSA

| | |
|--|--|
| Maximum Operating Voltage UL/CSA: | 500 V DC 480Y / 277 V AC |
| Connecting Capacity UL/CSA: | Busbar 14-8 AWG Conductor 14-4 AWG |
| Tightening Torque UL/CSA: | 25 in·lb |
| Interrupting Rating acc. to UL1077: | (220 V AC) 10 kA (277 V AC) 6 kA (440 V DC) 10 kA (480Y / 277 V AC) 10 kA (500 V DC) 10 kA |

Certificates and Declarations (Document Number)

| | |
|--|-----------------|
| Declaration of Conformity - CE: | 2CDK400583D2702 |
| Environmental Information: | 2CDK400030D201 |
| Instructions and Manuals: | 2CDC002142D0207 |

Container Information

| | |
|--------------------------------------|---------------|
| Package Level 1 Units: | 5 piece |
| Package Level 1 Width: | 92 mm |
| Package Level 1 Length: | 58 mm |
| Package Level 1 Height: | 80 mm |
| Package Level 1 Gross Weight: | 1.3 kg |
| Package Level 1 EAN: | 4013614424267 |
| Package Level 2 Units: | 60 piece |
| Package Level 2 Width: | 275 mm |
| Package Level 2 Length: | 395 mm |
| Package Level 2 Height: | 210 mm |
| Package Level 2 Gross Weight: | 16 kg |
| Package Level 2 EAN: | 4013614445200 |

Classifications

| | |
|------------------------------------|--|
| Object Classification Code: | F |
| ETIM 4: | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 5: | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 6: | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 7: | EC000042 - Miniature circuit breaker (MCB) |
| eClass: | 7.0 27141901 |
| UNSPSC: | 39121614 |

Accessories

| Identifier | Description | Type | Qty | Unit Of Measure |
|-------------------|--|--------------|------------|------------------------|
| 2CCA880100R0001 | CMS-100PS Sensor | CMS-100PS | 1 | piece |
| 2CCA880101R0001 | CMS-101PS Sensor | CMS-101PS | 1 | piece |
| 2CCA880102R0001 | CMS-102PS Sensor | CMS-102PS | 1 | piece |
| 2CDS200909R0001 | S2C-A1 - Shunt Trip | S2C-A1 | 1 | piece |
| 2CDS200909R0002 | S2C-A2 - Shunt Trip | S2C-A2 | 1 | piece |
| 2CDS200912R0001 | S2C-H6R - Auxiliary Contact | S2C-H6R | 1 | piece |
| 2CDS200918R0001 | S2C-NT - Hand Operated Neutral | S2C-NT | 1 | piece |
| 2CDS200922R0001 | S2C-S/H6R - Signal / Auxiliary Contact | S2C-S/H6R | 1 | piece |
| 2CDS200936R0001 | S2C-H11L - Auxiliary Contact | S2C-H11L | 1 | piece |
| 2CDS200936R0002 | S2C-H20L - Auxiliary Contact | S2C-H20L | 1 | piece |
| 2CDS200936R0003 | S2C-H02L - Auxiliary Contact | S2C-H02L | 1 | piece |
| 2CDS200946R0001 | S2C-H6-11R - Auxiliary Contact | S2C-H6-11R | 1 | piece |
| 2CDS200946R0002 | S2C-H6-20R - Auxiliary Contact | S2C-H6-20R | 1 | piece |
| 2CDS200946R0003 | S2C-H6-02R - Auxiliary Contact | S2C-H6-02R | 1 | piece |
| 2CDS200970R0001 | S2C-H01 - Auxiliary Contact | S2C-H01 | 1 | piece |
| 2CDS200970R0002 | S2C-H10 - Auxiliary Contact | S2C-H10 | 1 | piece |
| 2CSS200911R0001 | S2C-UA 12 DC - Undervoltage release | S2C-UA 12 DC | 1 | piece |
| 2CSS200911R0002 | S2C-UA 24 AC - Undervoltage release | S2C-UA 24 AC | 1 | piece |
| 2CSS200911R0003 | S2C-UA 48 AC - Undervoltage release | S2C-UA 48 AC | 1 | piece |

| Identifier | Description | Type | Qty | Unit Of Measure |
|-----------------|--------------------------------------|---------------|-----|-----------------|
| 2CSS200911R0004 | S2C-UA 110 AC - Undervoltage release | S2C-UA 110 AC | 1 | piece |
| 2CSS200911R0005 | S2C-UA 230 AC - Undervoltage release | S2C-UA 230 AC | 1 | piece |
| 2CSS200911R0006 | S2C-UA 400 AC - Undervoltage release | S2C-UA 400 AC | 1 | piece |
| 2CSS200911R0007 | S2C-UA 24 DC - Undervoltage release | S2C-UA 24 DC | 1 | piece |
| 2CSS200911R0008 | S2C-UA 48 DC - Undervoltage release | S2C-UA 48 DC | 1 | piece |
| 2CSS200911R0009 | S2C-UA 110 DC - Undervoltage release | S2C-UA 110 DC | 1 | piece |
| 2CSS200911R0010 | S2C-UA 230 DC - Undervoltage release | S2C-UA 230 DC | 1 | piece |
| 2CSS200998R0001 | S2C-BP - Mechanical tripping device | S2C-BP | 1 | piece |
| 2CSS200999R0001 | S2C-EST - Plug-in base | S2C-EST | 1 | piece |
| 2CSS201997R0013 | S2C-CM1 - Motor operating device | S2C-CM1 | 1 | piece |
| 2CSS203997R0013 | S2C-CM2/3 - Motor operating device | S2C-CM2/3 | 1 | piece |
| 2CSS204997R0013 | S2C-CM4 - Motor operating device | S2C-CM4 | 1 | piece |
| GHS2001901R0003 | S2C-DH - Mechanical Accessories | S2C-DH | 1 | piece |

