

Products → Low Voltage Products and Systems → Modular DIN Rail Products
→ Miniature Circuit Breakers MCBs Accessories → Shunt Trips

General Information

Extended Product Type:	S2C-A2U
Product ID:	2CDS200908R0002
EAN:	4016779644730
Catalog Description:	S2C-A2U - Shunt Trip
Long Description:	Remote opening of the device when a voltage is applied. Shunt trip only for range S 200 U and S 200 UP acc. UL 489 and CSA 22.2 No. 5.

Ordering

EAN:	4016779644730
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	17.5 mm
Product Net Height:	100 mm
Product Net Depth:	69 mm
Product Net Weight:	0.133 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	28 mm
Package Level 1 Height:	105 mm
Package Level 1 Length:	80 mm
Package Level 1 Gross Weight:	0.138 kg
Package Level 1 EAN:	4016779644730
Package Level 2 Units:	50 piece
Package Level 2 Width:	820 mm
Package Level 2 Height:	560 mm
Package Level 2 Length:	1200 mm
Package Level 2 Gross Weight:	7 kg
Package Level 2 EAN:	4016779946100

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
---------------------	---

Additional Information

Function:	Shunt Trip
Power Loss:	0 W
Product Main Type:	S2C
Product Name:	Shunt Trip
RoHS Date:	0335
Standards:	UL 489 CSA 22.2 No. 5
Suitable For:	S200U S200UP
Suitable for Product Class:	Miniature Circuit Breaker

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CSC000001D0201
Declaration of Conformity - CE:	2CDK400627D2701
Instructions and Manuals:	GHS2007010P0004
RoHS Information:	2CDK440033D0202

Classifications

eClass:	7.0 27143502
ETIM 4:	EC002303 - Shunt
ETIM 5:	EC001286 - Auxiliary contact unit for distribution board
ETIM 6:	EC001286 - Auxiliary contact unit for distribution board
UNSPSC:	39121614

