

General Information

Extended Product Type:	VBC7-30-01-F-04
Product ID:	GJL1313903R0014
EAN:	4013614217227
Catalog Description:	VBC7-30-01-F-04 Mini Reversing Contactor
Long Description:	The VBC7-30-01-F mini reversing contactor is a compact 3 pole contactor with 1 auxiliary contact, flat pin connection and normal mechanical interlock. They are ideally suited for applications where reliability is a must and space is at a premium. Mini reversing contactors are used in residential buildings, commercial buildings and industrial applications for the control of three-phase motor loads up to 5.5 kW (AC-3). Further features are the noiseless and hum-free coil, a switch position indication and the integrated possibility for rail or wall mounting.

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Popular Downloads

Data Sheet, Technical Information:	1SBC100173C0201
Instructions and Manuals:	2CDC102046M6801
Dimension Diagram:	GJL1200448F0001

Dimensions

Product Net Width:	96.5 mm
Product Net Height:	57.5 mm
Product Net Depth:	46.5 mm
Product Net Weight:	0.345 kg

Technical

Contactor Starter Type:	Compact Reversing Contactor with Normal Interlock
Number of Auxiliary Contacts NC:	1
Number of Auxiliary Contacts NO:	0
Number of Main Contacts NC:	0
Number of Main Contacts NO:	3
Number of Poles:	4

Pollution Degree:	3
Rated Frequency (f):	Main Circuit 60 Hz Main Circuit 50 Hz Main Circuit DC
Rated Impulse Withstand Voltage (U_{imp}):	Main Circuit 6 kV
Rated Insulation Voltage (U_i):	690 V acc. to UL/CSA 600 V
Rated Operational Current AC-1 (I_e):	(220 / 240 V) 40 °C 20 A (220 / 240 V) 55 °C 16 A (380 / 440 V) 40 °C 20 A (380 / 440 V) 55 °C 16 A (690 V) 40 °C 6 A (690 V) 55 °C 6 A
Rated Operational Current AC-3 (I_e):	(380 / 400 V) 55 °C 11.5 A
Rated Operational Voltage:	Auxiliary Circuit 12 ... 240 V DC Auxiliary Circuit 12 ... 500 V AC Main Circuit 690 V AC
Conventional Free-air Thermal Current (I_{th}):	Main Circuit 20 A
Rated Control Circuit Voltage (U_c):	110 ... 125 V DC
Coil Operating Limits:	(acc. to IEC 60947-4-1) for DC supply 0.85 ... 1.1 x U _c (at $\theta \leq 55$ °C)
Degree of Protection:	Main Circuit Terminals IP20
Mechanical Durability:	10000000 cycle
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Power Loss:	at Rated Operating Conditions per Pole 2 W
Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1

Environmental

Ambient Air Temperature:	Operation -20 ... +55 °C Storage -40 ... +80 °C
Maximum Operating Altitude Permissible:	2000 m
Resistance to Shock acc. to IEC 60068-2-27:	11 ms Pulse 15g
Resistance to Vibrations acc. to IEC 60068-2-6:	5g / 5 ... 150 Hz

RoHS Status:

Following EU Directive 2011/65/EU

Technical UL/CSA

**Maximum Operating Voltage
UL/CSA:**

Main Circuit 600 V AC

Horsepower Rating UL/CSA:

(208 V AC) Three Phase 3 Hp
(220 ... 240 V AC) Single Phase 1.5 Hp
(220 ... 240 V AC) Three Phase 3 Hp
(440 ... 480 V AC) Three Phase 5 Hp
(550 ... 600 V AC) Three Phase 5 Hp

General Use Rating UL/CSA:

(600 V AC) 16 A

Certificates and Declarations (Document Number)

BV Certificate:

1SAA920000-0204

CB Certificate:

1SAA938000-2002

CCC Certificate:

1SAA938001-3804

cUL Certificate:

cUL E191658

Declaration of Conformity - CE:

1SAD938512-0001

DNV GL Certificate:

1SAA938000-0306

EAC Certificate:

1SAA920000-2702

Instructions and Manuals:

2CDC102046M6801

KC Certificate:

1SAA938000-1501

LR Certificate:

1SAA938000-0504

RMRS Certificate:

1SAA938000-0704

RoHS Information:

1SAD938512-0001

Container Information

Package Level 1 Units:

5 piece

Package Level 1 Width:

115 mm

Package Level 1 Height:

54 mm

Package Level 1 Length:

280 mm

Package Level 1 Gross Weight:

1.795 kg

Package Level 1 EAN:

4013614419355

Classifications

Object Classification Code:

Q

ETIM 4:

EC000066 - Magnet contactor, AC-switching

ETIM 5:

EC000010 - Starter combination

ETIM 6:

EC000010 - Combination of contactors

ETIM 7:

EC000010 - Combination of contactors

eClass:

7.0 27371009

UNSPSC:

39121529

