

PSEN cs1.1p / PSEN cs1.1 1 Unit

540000



RFiD safety switch 2 safe semiconductor outputs, 8-pin M12 connector, four directions of actuation IP67, operating distance 21 mm, Sao = 15 mm, Sar = 40 mm, PU = 1 piece coded switch with actuator.

## Accessori opzionali



540319

PSEN cable axial M12 8-pole 3m



540320

PSEN cable axial M12 8-pole 5m



540321

PSEN cable axial M12 8-pole 10m



540322

PSEN cable angle M12 8-pole 3m



540323

PSEN cable angle M12 8-pole 5m



540324

PSEN cable angle M12 8-pole 10m



540325

PSEN cable angle M12 8-pole 30m



540326

PSEN cable axial M12 8-pole 30m



540331

PSEN T junction (auxiliary contact) M12



773603

PDP67 F 4 code



540311

PSEN screw M5x10 10pcs



540312

PSEN screw M5x20 10pcs



540340

PSEN cable M12-8sf M12-8sm, 2m



540341

PSEN cable M12-8sf M12-8sm, 5m



540343

PSEN cable M12-8sf M12-8sm, 20m



540344

PSEN cable M12-8sf M12-8sm, 30m

---



540342

PSEN cable M12-8sf M12-8sm, 10m

---



540333

PSEN cable M12-8sf, 20m

---



540130

SDD ES ETH

---



540132

SDD ES PROFIBUS

---



540338

PSEN Y junction M12-M12/M12 PIGTAIL

---