NSYCR20WU1C

ClimaSys PTC heating resistance 20W, 12-24V insulate





Main	
Range	ClimaSys
Product name	ClimaSys CR
Product or Component Type	Resistance heater
Power range	20 W
Input voltage	1224 V DC
Electrical connection	4 screw terminals 2.5 mm²

Complementary

Vertical	
-40158 °F (-4070 °C)	
IP20	
Class II	
VDE UL	
Body extruded aluminium Cover plastic	
External 3.86 in (98 mm)	
External 1.50 in (38 mm)	
External 2.95 in (75 mm)	
Heaters must be installed with a thermal controller Electrical protection is needed Air sealed enclosure	
By clips	
35 mm DIN rail	
	-40158 °F (-4070 °C) IP20 Class II VDE UL Body extruded aluminium Cover plastic External 3.86 in (98 mm) External 1.50 in (38 mm) External 2.95 in (75 mm) Heaters must be installed with a thermal controller Electrical protection is needed Air sealed enclosure By clips

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES	
Discount Schedule	ES1	
GTIN	3606480152269	
Returnability	No	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.77 in (4.5 cm)	
Package 1 Width	3.15 in (8 cm)	
Package 1 Length	4.33 in (11 cm)	
Package 1 Weight	7.20 oz (204 g)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	10	
Package 2 Height	7.87 in (20 cm)	
Package 2 Width	11.81 in (30 cm)	

Package 2 Length	15.75 in (40 cm)
Package 2 Weight	4.50 lb(US) (2.04 kg)
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------