VW3M3501

eSM safety card - for Lexium 32 servo drive - 24 V DC





Main

Range Compatibility	Lexium 32
Accessory / separate part category	Communication option
Accessory / Separate Part Type	ESM safety card
Product or Component Type	ESM safety card
Product Compatibility	Lexium 32
Accessory / separate part destination	Servo drive
[Us] rated supply voltage	24 V DC 1930 V
Discrete input number	11

Complementary

Discrete output number	7
Voltage state 0 guaranteed	<= 5 V
Voltage state 1 guaranteed	>= 15 V
Reverse polarity protection	Yes on input
Short-circuit protection	Yes on output
Safety Function	SOS (safe operating stop) SLS (safe limited speed) SS1 (safe stop 1) STO (safe torque off) SS2 (safe stop 2)
Safety level	SIL 3 EN/IEC 61508 SILCL 3 EN/IEC 62061 PL = e ISO 13849-1

Environment

Standards	EN/IEC 61508	
	ISO 13849-1	
	EN/IEC 62061	

Ordering and shipping details

Category	18263-LEXIUM 32 ACCESSORIES
Discount Schedule	PC51
GTIN	3606480169694
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.68 in (6.8 cm)	
Package 1 Width	5.12 in (13.0 cm)	
Package 1 Length	7.48 in (19.0 cm)	
Package 1 Weight	4.66 oz (132.0 g)	
Unit Type of Package 2	S04	

Number of Units in Package 2	36	
Package 2 Height	11.81 in (30.0 cm)	
Package 2 Width	15.75 in (40.0 cm)	
Package 2 Length	23.62 in (60.0 cm)	
Package 2 Weight	12.40 lb(US) (5.623 kg)	
Offer Sustainability		

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	[™] REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	
PVC free	Yes	

ontractual warranty	
Warranty	18 months