



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Battery Type	Lead-Acid battery
Provided Equipment	Documentation CD User Manual Warranty card

Physical

Color	Black
Height	17.01 in (43.2 cm)
Width	3.35 in (8.5 cm)
Depth	23.39 in (59.4 cm)
Net Weight	89.51 lb(US) (40.6 kg)
Mounting Mode	Rack-mounted with kit

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 % non-condensing
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 % non-condensing

Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Battery Voltage	96V
RBC Quantity	2

Ordering and shipping details

GTIN	731304317722
------	--------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.41 in (23.9 cm)
Package 1 Width	32.72 in (83.1 cm)
Package 1 Length	23.58 in (59.9 cm)
Package 1 Weight	98.11 lb(US) (44.5 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------