
# DF22AM1

Auxiliary contact block, TeSys DF, 1NC, 5A, disconnector, signalling contact, instantaneous





# Main Range TeSys Device short name DF22 Product or Component Type Auxiliary contacts operation Pole contact 1 NC composition

Faston connector

Com	plemen	itary

Range compatibility	TeSys (TeSys DF)	
[Ui] rated insulation voltage	250 VAC	
[Ue] rated operational voltage	24240 V AC AC-15 24240 V DC DC-13	
[lth] conventional free air thermal current	5 A	
Minimum switching current	30 mA	
Minimum switching voltage	10 V	
Net Weight	0.07 lb(US) (0.032 kg)	

Connections - terminals

### **Environment**

Ambient Air Temperature for Operation	-4140 °F (-2060 °C)
Ambient Air Temperature for Storage	-40176 °F (-4080 °C)

### Ordering and shipping details

Category	21714-DF FUSEHOLDERS
Discount Schedule	CP1
GTIN	3389119407564
Returnability	No
Country of origin	TN

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.26 in (3.2 cm)
Package 1 Width	4.13 in (10.5 cm)
Package 1 Length	0.79 in (2.0 cm)
Package 1 Weight	0.92 oz (26.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	100
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	6.89 lb(US) (3.124 kg)

# Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: Cancer - www.P65Warnings.ca.gov	
REACh Regulation	☑REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

## Contractual warranty

Warranty	18 months
----------	-----------