# NSYZZ274G

# Polyester glassreinf. plinth for encl. PLAZ(T)74 front opening IP44-IK10 RAL7035





#### Main

· · · · · · · · · · · · · · · · · · ·	
Range	Thalassa
Accessory / separate part category	Enclosure accessory
Product or Component Type	Plinth
Anwendung	Multi-purpose
Nennmaße des Gehäuses	- D: 16.54 in (420 mm)
Device composition	Fixing elements 2 front panel 2 side part
Range compatibility	Thalassa (Thalassa PLA) Thalassa (Thalassa PHD)

# Complementary

Fixing mode	By screws - on side parts
Color	Plinth Gray RAL 7035)
Height	7.87 in (200 mm)
Width	30.91 in (785 mm)
Depth	16.14 in (410 mm)

#### Environment

IP degree of protection	IP44
IK degree of protection	IK10

# Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480726286
Returnability	No

# **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.54 in (9.0 cm)	
Package 1 Width	16.93 in (43.0 cm)	
Package 1 Length	32.68 in (83.0 cm)	
Package 1 Weight	17.08 lb(US) (7.747 kg)	

# Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Mercury free	Yes	
China RoHS Regulation	☐ China RoHS Declaration	

RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Combined to all the month.		
Contractual warranty		
Warranty	18 months	