VW3L30010R200

cable for STO safety function - 20m - 1 female connector - M8





Main

TTT COLUMN	
Range of Product	Lexium integrated drive
Product or Component Type	Cable for safe torque off safety function for industrial connector
Accessory / Separate Part Type	Cable
Accessory / separate part category	Connection accessories
Accessory / separate part destination	For drives with industrial connectors for safe torque off
Cable length	65.62 ft (20 m)

Complementary

Electrical connection	1 female connector M8, 4 pins
Net Weight	1.34 lb(US) (0.608 kg)

Ordering and shipping details

Category	18289-LEXIUM INTEGRATED DRIVES ACC
Discount Schedule	PC56
GTIN	3389118367661
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.57 in (4.0 cm)
Package 1 Width	7.87 in (20.0 cm)
Package 1 Length	7.87 in (20.0 cm)
Package 1 Weight	21.45 oz (608.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	20
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	28.38 lb(US) (12.873 kg)

Offer Sustainability

Contractual warranty

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End Of Life Information
PVC free	Yes

18 months