VZ14

TeSys VARIO - additional earthing block - 40 A - for V02...V2





Main

Range	TeSys
Device short name	VZ
Product or Component Type	Additional earthing block
Performance level	High performance
Contacts type and composition	Without
Product Compatibility	V0 V02 V2 V01 V1
Network type	AC DC
Network Frequency	50/60 Hz

Complementary

Mounting Location	Right Left
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	6 kV
[Ith] conventional free air thermal current	40 A
Connections - terminals	Screw clamp terminals
Height	2.91 in (74 mm)
Width	0.63 in (16 mm)
Depth	1.38 in (35 mm)
Net Weight	0.11 lb(US) (0.05 kg)

Environment

Standards	IEC 60947-3	
Product Certifications	UL GL CSA UKCA	
Protective treatment	TC	
IP degree of protection	IP20 conforming to IEC 60529	
Mechanical robustness	Vibrations 10150 Hz 5 gn) IEC 60068-2-6 Shocks 11 ms 15 gn) IEC 60068-2-27	
Ambient Air Temperature for Operation	-4122 °F (-2050 °C)	
Fire resistance	1760 °F (960 °C) IEC 60695-2-1	

Ordering and shipping details

Category	21730-V VARIO SWITCH	
Discount Schedule	CP1	
GTIN	3389110551938	
Returnability	Yes	
Country of origin	CZ	

Packing Units

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.17 in (5.5 cm)
Package 1 Width	1.46 in (3.7 cm)
Package 1 Length	3.54 in (9.0 cm)
Package 1 Weight	1.55 oz (44.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	69
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	7.44 lb(US) (3.376 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes
Halogen content performance	Halogen free product

Contractual warranty

vvarranty 18 months
