NSYCMACS50

Signalling beacon adapter, square 50 mm RAL 7040. For S3CM HMI encl.





Main	
Range	Spacial
Accessory / separate part category	Mounting accessory
Product or Component Type	Adaptor for signalling beacon
Device Application	Multi-purpose
Enclosure nominal dimensions	-
Mounting Location	On fixed brackets
Mounting Support	Signalling beacon Option of passing cables through the inside For 50 mm square tube
Range compatibility	Spacial (Spacial S3CM)
Device composition	1 adaptor 1 nut

Set of 1

Complementary

- Complementary		
Material	Adaptor aluminium	
Color	Adaptor Gray RAL 7040)	
Surface Finish	Epoxy-polyester powder	
Fixing mode	Direct fixing - on fixed brackets of enclosure	
Permanent permissible load	0.06 lb(US) (0.025 kg)	
Height	0.00 in (0 mm)	
Diameter	0.55 in (14 mm)	
Net Weight	0.24 lb(US) (0.11 kg)	

Quantity per Set

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480213267
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.74 in (9.5 cm)	
Package 1 Width	5.98 in (15.2 cm)	
Package 1 Length	6.10 in (15.5 cm)	
Package 1 Weight	3.88 oz (110.0 g)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	10	
Package 2 Height	7.87 in (20.0 cm)	
Package 2 Width	11.81 in (30.0 cm)	
Package 2 Length	15.75 in (40.0 cm)	
Package 2 Weight	1322.77 lb(US) (600.0 kg)	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
wantanty	TO MONUTE