

Product data sheet

Characteristics

9422A7

Operating mechanism, flange mounted, variable depth, handle mechanism, 12in handle, NEMA 1, 3R, 4, 12 enclosure



Main

Product	Handle Mechanism
For Use With	9422TG2 disconnect switch 9422TG1 disconnect switch

Complementary

Product Type	Variable depth
Product destination	9422TG1 disconnect switch 9422TG2 disconnect switch
Enclosure Types	NEMA 1/3/3R/4/12 enclosures
Handle Length	12 in (304.80 mm)

Ordering and shipping details

Category	21732-9422
Discount Schedule	CP1
GTIN	785901624899
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.82 in (22.4 cm)
Package 1 Width	11.18 in (28.4 cm)
Package 1 Length	19.49 in (49.5 cm)
Package 1 Weight	6.00 lb(US) (2.72 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	32
Package 2 Height	40.00 in (101.6 cm)
Package 2 Width	36.00 in (91.44 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	192.00 lb(US) (87.09 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------