

9001K43J35LRFR

Illuminated selector switch head, Harmony
9001K, metal, long handle, red, 30mm, 3
positions, stay put, LED red, 24-28V



Main

| | |
|---------------------------|--------------------------------------|
| Range of Product | Harmony 9001K |
| Product or Component Type | Head for illuminated selector switch |
| Device short name | 9001K |
| Type of operator | Stay put |
| Operator profile | Red long handle |

Complementary

| | |
|-------------------------------|------------------------|
| Bezel material | Metal |
| Mounting diameter | 1.18 in (30 mm) |
| Net Weight | 0.54 lb(US) (0.245 kg) |
| Shape of signaling unit head | Octagonal |
| Operator position information | 3 positions |
| Contacts type and composition | Without contact block |
| Mechanical durability | 500000 cycles |
| Light block supply | Direct |
| Light source | LED |
| Bulb base | BA 9s |
| Light block colour | Red |
| [Us] rated supply voltage | 24 V AC/DC |
| Product compatibility | 9001KA1 side 1 or 2 |
| Device presentation | Basic element |

Environment

| | |
|---------------------------------------|--|
| Protective treatment | TC |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C) |
| Electrical shock protection class | Class II IEC 61140 |
| IP degree of protection | IP66 IEC 60529 |
| NEMA degree of protection | NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3R NEMA 4 |
| Standards | EN/IEC 60947-5-4 CSA C22.2 No 14 JIS C 852 JIS C 4520 EN/IEC 60947-1 UL 508 EN/IEC 60947-5-1 |

| | |
|------------------------|-------------------------------|
| Product Certifications | UL 508 NEMA |
| Vibration resistance | 7 gn 2...500 Hz)IEC 60068-2-6 |
| Shock resistance | 50 gn IEC 60068-2-27 |

Ordering and shipping details

| | |
|-------------------|-----------------------------|
| Category | 21426-9001 K (NOT KA,KM,KX) |
| Discount Schedule | CS1 |
| GTIN | 3389118042964 |
| Returnability | No |
| Country of origin | MX |

Packing Units

| | |
|------------------------------|---------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.80 in (4.572 cm) |
| Package 1 Width | 2.10 in (5.334 cm) |
| Package 1 Length | 3.60 in (9.144 cm) |
| Package 1 Weight | 8.80 oz (249.476 g) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|