

# NSYTRV352PE

## SCREW TERMINAL, PROTECTIVE EARTH, 2 POINTS, 35MM<sup>2</sup>, GREEN-YELLOW



### Main

Range	Lineryg
Product name	Lineryg TR
Product or Component Type	Terminal block
Device short name	TRV
Terminal block type	Protective earth
Terminal block level	1
Mounting Mode	Clip-on
Nominal cross section	0.05 in <sup>2</sup> (35 mm <sup>2</sup> )
Length	2.59 in (65.7 mm)
Color	Green-yellow
Quantity per Set	Set of 50

### Complementary

Width	0.63 in (16 mm)
Height	2.37 in (60.2 mm)
Connections - terminals	1 x screw terminal upstream 1 x screw terminal downstream
Number of connections	2
Connection position	Sideways
Number of measurement input	2
Cable cross section	0.00...0.08 In <sup>2</sup> (1.5...50 mm <sup>2</sup> ), solid 0.00...0.05 In <sup>2</sup> (2.5...35 mm <sup>2</sup> ), flexible with cable end 0.00...0.08 in <sup>2</sup> (1.5...50 mm <sup>2</sup> ), flexible without cable end
Tightening torque	28.32...32.75 lbf.in (3.2...3.7 N.m)
Wire stripping length	0.71 in (18 mm)
Tool type	Connection screwdriver Disconnection screwdriver
Line Rated Current	125 A EN/IEC 60947-7-1
Material	Polyamide 6/6 insulating case
Dielectric loss	0.01 at 1 MHz IEC 60250 0.01 at 1 MHz VDE 0303-T4
Dielectric constant	3.7 at 1 MHz
Resistivity	10000 MΩ.M IEC 60093 10000 MΩ.m VDE 0303-T30
Surface resistance	1000 GΩ IEC 60093 1000 GΩ VDE 0303-T30
Creep resistance	500 CTI (> 400 kV) IEC 60093 500 CTI (> 400 kV) VDE 0303-T30
Flame retardance	V0 0.03 in (0.8 mm) UL 94
Net Weight	3.03 oz (85.79 g)
Range compatibility	Prisma G Prisma P Prisma PH Prisma Pack Spacial Kaedra Pragma TeSys
Product Compatibility	Spacial enclosures

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Product Certifications	VDE EAC CSA CURus IEC-Ex GL ATEX
Dielectric strength	1000 V IEC 60243-1
Ambient air temperature for operation	-40...266 °F (-40...130 °C) IEC 60216-1 -40...266 °F (-40...130 °C) VDE 0304-T21

## Ordering and shipping details

Category	21715-IEC TERMINAL BLOCKS-NSY,AM1,DF6,GK1
Discount Schedule	CP5
GTIN	3606480532177
Returnability	No
Country of origin	TR

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.74 in (9.500 cm)
Package 1 Width	7.09 in (18.000 cm)
Package 1 Length	11.02 in (28.000 cm)
Package 1 Weight	3.00 oz (85.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	50
Package 2 Height	3.74 in (9.500 cm)
Package 2 Width	7.09 in (18.000 cm)
Package 2 Length	11.02 in (28.000 cm)
Package 2 Weight	9.74 lb(US) (4.418 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	1700
Package 3 Height	29.53 in (75.000 cm)
Package 3 Width	23.62 in (60.000 cm)
Package 3 Length	31.50 in (80.000 cm)
Package 3 Weight	356.22 lb(US) (161.580 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

---

Warranty	18 months
----------	-----------

---