NSYZZ2124G

Polyester glassreinf. plinth for encl PLAZ(T)124 front opening IP44-IK10 RAL7035





Main

Range	Thalassa
Accessory / separate part category	Enclosure accessory
Product or Component Type	Plinth
Anwendung	Multi-purpose
Nennmaße des Gehäuses	- D: 16.54 in (420 mm)
Device composition	Fixing elements 2 front panel 2 side part
Range compatibility	Thalassa (Thalassa PLA) Thalassa (Thalassa PHD)

Complementary

Fixing mode	By screws - on side parts
Color	Plinth Gray RAL 7035)
Height	7.87 in (200 mm)
Width	50.59 in (1285 mm)
Depth	16.14 in (410 mm)

Environment

IP degree of protection	IP44
IK degree of protection	IK10

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480726309
Returnability	No

Packing Units

PCE
1
3.54 in (9.0 cm)
18.11 in (46.0 cm)
50.79 in (129.0 cm)
21.94 lb(US) (9.95 kg)

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Mercury free	Yes	
China RoHS Regulation	☐ China RoHS Declaration	

RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Combined to all the month.		
Contractual warranty		
Warranty	18 months	