## Product data sheet Characteristics

# VW3L50010

# connector 1 safe torque off output - 1 connector M8 4 pins



Connector 1 safe torque off output
Connector
Connection accessories
Connector for safe torque off safety function signals

#### Complementary

o o mpromontary		
Range Compatibility	Lexium ILA	
	Lexium ILS	
	Lexium 32i	
	Lexium ILE	
Kit composition	1 connector M8 4 pins	
Net Weight	0.04 lb(US) (0.018 kg)	

## Ordering and shipping details

Category	18289-LEXIUM INTEGRATED DRIVES ACC
Discount Schedule	PC56
GTIN	3389118367807
Returnability	No
Country of origin	CZ

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	0.98 in (2.5 cm)	
Package 1 Width	1.38 in (3.5 cm)	
Package 1 Length	4.33 in (11.0 cm)	
Package 1 Weight	0.56 oz (16.0 g)	
Unit Type of Package 2	S01	
Number of Units in Package 2	10	
Package 2 Height	5.91 in (15.0 cm)	
Package 2 Width	5.91 in (15.0 cm)	
Package 2 Length	15.75 in (40.0 cm)	
Package 2 Weight	12.06 oz (342.0 g)	

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫ <sub>Yes</sub>
PVC free	Yes

#### Contractual warranty

Contraction Warranty	
Warranty	18 months