# **NSYTVR7**

Vertical uprights height 750mm. zinc-coated steel. Supply: 2 standard uprights.





Main	
Range	Thalassa
Accessory / separate part category	Mounting accessory
Product or Component Type	Technical upright
Device application	Multi-purpose
Enclosure nominal dimensions	-
Mounting Support	Direct fixing on the rear inserts Step slide
Range compatibility	Thalassa (Thalassa PLA)
Device composition	2 upright
Material	steel

#### Complementary

Surface Finish	Zinc coated	
Fixing mode	Bosses inserts M8 - rear of enclosure	
Adjustment	Adjustable in height every 2.5 mm with quarter-turn nuts	
Height	Nominal 29.53 in (750 mm) Real 24.61 in (625 mm)	
Width	1.77 in (45 mm)	
Depth	1.34 in (34 mm)	
Thickness	0.08 in (2 mm)	
Cut-out dimensions	11 x 13 mm	

#### Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480185083
Returnability	No
Country of origin	FR

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.38 in (3.5 cm)
Package 1 Width	2.36 in (6.0 cm)
Package 1 Length	24.80 in (63.0 cm)
Package 1 Weight	4.16 lb(US) (1.886 kg)
Unit Type of Package 2	PAM
Number of Units in Package 2	60
Package 2 Height	19.69 in (50.0 cm)
Package 2 Width	39.37 in (100.0 cm)
Package 2 Length	47.24 in (120.0 cm)
Package 2 Weight	277.78 lb(US) (126.0 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile

## Contractual warranty

Warranty	18 months
wantanty	TO MONUTE