



## Main

|                                |                              |
|--------------------------------|------------------------------|
| Range of Product               | Harmony XB4                  |
| Product or Component Type      | Head for joystick controller |
| Device short name              | ZB4                          |
| Bezel material                 | Chromium plated metal        |
| Mounting diameter              | 0.87 in (22 mm)              |
| Sale per indivisible quantity  | 1                            |
| Shape of signaling unit head   | Round                        |
| Type of operator               | Stay put                     |
| Operator profile               | 54 mm long operating shaft   |
| Operator direction information | 4 directions                 |

## Complementary

|                                    |   |
|------------------------------------|---|
| Net Weight                         | 0.05 lb(US) (0.022 kg)                        |
| Resistance to high pressure washer | 1015.26 psi (7000000 Pa) 131 °F (55 °C) 0.1 m |
| Operator position information      | 5 positions                                   |
| Mechanical durability              | 1000000 cycles                                |
| Device presentation                | Basic element                                 |

## Environment

|                                       |   |
|---------------------------------------|---|
| Protective treatment                  | TH  |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)  |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C)  |
| Electrical shock protection class     | Class I IEC 60536   |
| IP degree of protection               | IP66 IEC 60529  |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X  |
| IK degree of protection               | IK03 IEC 50102  |
| Standards                             | JIS C8201-5-1<br>EN/IEC 60947-5-5<br>UL 508<br>EN/IEC 60947-5-4<br>EN/IEC 60947-1<br>EN/IEC 60947-5-1<br>CSA C22.2 No 14<br>JIS C8201-1 |
| Product Certifications                | UL Listed<br>DNV<br>LROS (Lloyds register of shipping)<br>GL<br>CSA<br>BV   |
| Vibration resistance                  | 5 gn 2...500 Hz)IEC 60068-2-6   |
| Shock resistance                      | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>50 gn 11 ms) half sine wave acceleration IEC 60068-2-27                      |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Ordering and shipping details

|                   |                                       |
|-------------------|---------------------------------------|
| Category          | 22469-PUSHBUTTON,22MM ACCESSORIES-NEW |
| Discount Schedule | CS2                                   |
| GTIN              | 3389110119916                         |
| Returnability     | No                                    |
| Country of origin | FR                                    |

## Packing Units

|                              |                  |
|------------------------------|------------------|
| Unit Type of Package 1       | PCE              |
| Number of Units in Package 1 | 1                |
| Package 1 Height             | 3.46 in (8.8 cm) |
| Package 1 Width              | 1.34 in (3.4 cm) |
| Package 1 Length             | 2.13 in (5.4 cm) |
| Package 1 Weight             | 2.12 oz (60.0 g) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|