



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



### Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product Compatibility	XCKT XCKP XCMD XCKD

Associated body	ZCP26 ZCP29 ZCP37 ZCD27 ZCMD41L5 ZCMD39L2 ZCMD21L08R12 ZCT25N12 ZCP21M12 ZCD28 ZCMD69C12 ZCMD61C12 ZCD25 ZCT27G11 ZCD37 ZCT28N12 ZCMD39L5 ZCT27P16 ZCMD25L1 ZCP21 ZCMD37L5 ZCMD25L5 ZCP29M12 ZCMD21L08U78 ZCD29M12 ZCD21 ZCD39 ZCT28G11 ZCMD37L1 ZCMD81L1 ZCMD61M12 ZCMD37L2 ZCT28P16 ZCT26N12 ZCMD29C12 ZCT21N12 ZCP31 ZCT25G11 ZCMD21M12 ZCT26P16 ZCMD41L1 ZCMD21L5 ZCMD21L2 ZCMD29L5 ZCMD21L1 ZCD29 ZCT21P16 ZCP27 ZCP28 ZCP35 ZCP39 ZCP25 ZCMD29L2 ZCD35 ZCT26G11 ZCD21M12 ZCD26 ZCT25P16 ZCMD25L2 ZCMD81L5 ZCT27N12 ZCMD81L2 ZCD31 ZCMD21C12 ZCMD41L2 ZCMD29L1 ZCT21G11 ZCMD39L1
Movement of operating head	Linear
Type of operator	Side plunger spring return metal
Type of approach	Vertical approach, 1 direction

## Complementary

Positive opening With

## Environment

Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

## Ordering and shipping details

Category	22413-LIMIT SWITCH, IEC, MINIATURE
Discount Schedule	T
GTIN	3389110191431
Returnability	No
Country of origin	ID

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.71 in (1.8 cm)
Package 1 Width	1.65 in (4.2 cm)
Package 1 Length	1.26 in (3.2 cm)
Package 1 Weight	1.90 oz (54.0 g)
Unit Type of Package 2	BAG
Number of Units in Package 2	10
Package 2 Height	1.97 in (5.0 cm)
Package 2 Width	3.15 in (8.0 cm)
Package 2 Length	5.12 in (13.0 cm)
Package 2 Weight	19.05 oz (540.0 g)
Unit Type of Package 3	S01
Number of Units in Package 3	90
Package 3 Height	5.91 in (15.0 cm)
Package 3 Width	5.91 in (15.0 cm)
Package 3 Length	15.75 in (40.0 cm)
Package 3 Weight	11.25 lb(US) (5.102 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------