



Main

| | |
|---------------------------------------|--|
| Product or Component Type | Pre-assembled cable kits for pulse/direction interface |
| Accessory / Separate Part Type | Cable |
| Accessory / separate part category | Connection accessories |
| Accessory / separate part destination | For drives with printed circuit board connectors and pulse/direction interface |
| Cable length | 9.84 ft (3 m) |
| Additional information | With integrated cable entry with strain relief |

Complementary

| | |
|-------------------------|---|
| Range Compatibility | Lexium ILS Lexium ILA Lexium ILE |
| Product Compatibility | ILS1 |
| Communication interface | Pulse/direction |
| Electrical connection | Printed circuit board connector drive Cable end open |
| Net Weight | 1.20 lb(US) (0.544 kg) |

Ordering and shipping details

| | |
|-------------------|------------------------------------|
| Category | 18289-LEXIUM INTEGRATED DRIVES ACC |
| Discount Schedule | PC56 |
| GTIN | 3389118367357 |
| Returnability | No |
| Country of origin | CZ |

Packing Units

| | |
|------------------------------|-------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.57 in (4 cm) |
| Package 1 Width | 9.84 in (25 cm) |
| Package 1 Length | 9.84 in (25 cm) |
| Package 1 Weight | 19.19 oz (544 g) |
| Unit Type of Package 2 | S04 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 11.81 in (30 cm) |
| Package 2 Width | 15.75 in (40 cm) |
| Package 2 Length | 23.62 in (60 cm) |
| Package 2 Weight | 14.75 lb(US) (6.692 kg) |
| Package 3 Height | 28.94 in (73.5 cm) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

| | |
|----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|