## Product data sheet Characteristics

### VW3M9420

# Cable, Lexium 32i, preassembled for STO safety function, 20 m, M8





Main	
Range of Product	Lexium 32i
Product or Component Type	Cable
Accessory / separate part category	Connection accessory
Product compatibility	Connector module VW3M91 safe torque off safety function Connector module VW3M92 safe torque off safety function

#### Complementary

Cable length	65.62 ft (20 m)	
Electrical connection	M8 female connector, 1	
	Free end, 1	
Cable composition	3 x 0.34 mm²	
Standards	IEC 61800-5-2	
Wire colour	White STO_A	
	Brown STO_B	
	Green STO_COM	
Net Weight	1.51 lb(US) (0.684 kg)	

#### Ordering and shipping details

Category	18289-LEXIUM INTEGRATED DRIVES ACC
Discount Schedule	PC56
GTIN	3606480595615
Returnability	No
Country of origin	CZ

#### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.97 in (5.0 cm)
Package 1 Width	11.81 in (30.0 cm)
Package 1 Length	16.93 in (43.0 cm)
Package 1 Weight	24.13 oz (684.0 g)
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	15.75 in (40.0 cm)
Package 2 Length	23.62 in (60.0 cm)
Package 2 Weight	11.81 lb(US) (5.356 kg)

#### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
PVC free	Yes