



### Main

Range	ClimaSys
Product name	CU
Product or Component Type	Cooling unit
Mounting type	Side
Type of Installation	Outdoor
Product destination	For enclosure
Mounting Mode	By screws
Input voltage	230 V 50/60 Hz
Phase	1 phase
Cooling power	380 W 50/60 Hz L35-L35 240 W 50/60 Hz L35-L50

### Complementary

Height	18.11 in (460 mm)
Width	11.22 in (285 mm)
Depth	7.09 in (180 mm)
Line Rated Current	1.6 A
Inrush current	6 A
Power consumption in W	440 W 50/60 Hz, L35-L35 490 W 50/60 Hz, L35-L50
Energy efficiency ratio	1.4
Control Type	Mechanical
Temperature setting range	68...131 °F (20...55 °C)
Ambient air temperature for operation	Inside the enclosure 68...115 °F (20...46 °C) Maximum 131 °F (55 °C) Outside the enclosure -4...131 °F (-20...55 °C)
Noise level	61 dB EN/ISO 3746
Pressure	377.10 psi (26 bar)
Flow rate	Internal circuit 73969.50 Gal/hr(US) (280 m3/h) 50/60 Hz External circuit 73969.50 Gal/hr(US) (280 m3/h) 50/60 Hz
Net Weight	37.48 lb(US) (17 kg)
Cooling gas type	R134a 0.29 lb(US) (0.13 kg))
Type of filter	Optional external circuit filter
Protection type	Thermal protection T 4 A Short-circuit protection (magnetic)
Material	Steel
Color	Gray RAL 7035)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Product Certifications	CE
Directives	2006/42/EC - machinery 2004/108/EC - electromagnetic compatibility 2006/95/EC - low voltage directive
Standards	EN 60335-2-40 EN 60335-1 EN/ISO 12100 EN 60204-1 EN 378
IP degree of protection	IP55 IEC 60529 on the internal circuit) IP34 IEC 60529 on the external circuit)

## Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480676789
Returnability	No
Country of origin	ES

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.09 in (18.0 cm)
Package 1 Width	11.22 in (28.5 cm)
Package 1 Length	18.11 in (46.0 cm)
Package 1 Weight	37.48 lb(US) (17.0 kg)
Unit Type of Package 2	P12
Number of Units in Package 2	16
Package 2 Height	55.91 in (142.0 cm)
Package 2 Width	31.50 in (80.0 cm)
Package 2 Length	47.24 in (120.0 cm)
Package 2 Weight	645.95 lb(US) (293.0 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.