



Main

Accessory / separate part category	Cabling accessory
Accessory / Separate Part Type	Jumper cable

Complementary

Jumper cable end 1	M12 male 5 pins straight screw-on
Jumper cable end 2	M12 female 5 pins straight screw-on
Collar material	Metal
Cable composition	5 x 0.25 mm ²
Cable length	1.64 ft (0.5 m)
Wire insulation material	PVC
Cable outer diameter	0.20 in (5 mm)
[Ue] rated operational voltage	30 V DC
Line Rated Current	1.5 A
Insulation resistance	>= 100 MOhm
Maximum resistance across terminals	10 mOhm
Net Weight	0.15 lb(US) (0.07 kg)

Environment

IP Degree of Protection	IP65 IP67
Ambient air temperature for operation	-22...176 °F (-30...80 °C) static
Ambient Air Temperature for Storage	-22...176 °F (-30...80 °C)

Ordering and shipping details

Category	22483-MACHINE CABLES
Discount Schedule	DS3
GTIN	3389119646611
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.79 in (2.0 cm)
Package 1 Width	3.94 in (10.0 cm)
Package 1 Length	4.72 in (12.0 cm)
Package 1 Weight	2.12 oz (60.0 g)
Unit Type of Package 2	S01

Number of Units in Package 2	6
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	5.91 in (15.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	19.68 oz (558.0 g)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information