

# Product data sheet

## Characteristics

# VW3M5104R250

power cable- between servomotor BSH and servodrive - 4 x 10 mm<sup>2</sup> + 2 x 1 mm<sup>2</sup> -25m



### Main

|                                       |  |
|---------------------------------------|--|
| Product or Component Type             | Power cable  |
| Accessory / Separate Part Type        | Preassembled power cordset   |
| Accessory / separate part category    | Connection accessory   |
| Product compatibility                 | Servo motor BMH, 2 7.48 in (190 mm))B2 EN 60204-1<br>Servo motor BMH, 3 7.48 in (190 mm))B2 EN 60204-1 |
| Accessory / separate part destination | Between servo motor and servo drive  |
| Range Compatibility                   | Lexium 32  |
| Cable length                          | 82.02 ft (25 m)  |
| Cable composition                     | 4 x 10 mm <sup>2</sup> + 2 x 1 mm <sup>2</sup>   |

### Complementary

|                       |  |
|-----------------------|--|
| Electrical connection | Free end servo drive side<br>Connector - industrial M40 servo motor side |
| Net Weight            | 54.01 lb(US) (24.5 kg)   |

### Ordering and shipping details

|                   |                                      |
|-------------------|--------------------------------------|
| Category          | 18310-MOTION CONTROL MOTORS & ACCESS |
| Discount Schedule | PC53                                 |
| GTIN              | 3389119210935                        |
| Returnability     | No                                   |
| Country of origin | CZ                                   |

### Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | PCE                    |
| Number of Units in Package 1 | 1                      |
| Package 1 Height             | 7.87 in (20.0 cm)      |
| Package 1 Width              | 23.62 in (60.0 cm)     |
| Package 1 Length             | 23.62 in (60.0 cm)     |
| Package 1 Weight             | 48.50 lb(US) (22.0 kg) |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.