



Overview

Lead time	Usually in Stock
-----------	------------------



Main

Number of rack unit	3U
Battery Type	Lead-Acid battery
Provided Equipment	Installation guide Warranty card Rack Mounting brackets

Physical

Color	Black
Height	5.12 in (13 cm)
Width	17.01 in (43.2 cm)
Depth	26.88 in (68.27 cm)
Net Weight	200.62 lb(US) (91 kg)
Mounting Mode	Rack-mounted

Conformance

Standards	OSHDP
-----------	-------

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 % non-condensing
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 % non-condensing

Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Stand alone battery stack
Battery Voltage	+/- 192 V
RBC Quantity	2

Ordering and shipping details

GTIN	731304292753
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.54 in (42 cm)
Package 1 Width	23.62 in (60 cm)
Package 1 Length	39.37 in (100 cm)
Package 1 Weight	232.59 lb(US) (105.5 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------