# **HU362DS**

Safety switch, heavy duty, non fusible, 60A, 3 wire, 3 poles, 60hp, 600VAC/DC, Type 4, 4X, 5, 304 stainless steel





#### Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device Application	Heavy application
Disconnect Type	Non-fusible disconnect
Factory Installed Neutral	None
Phase	3 phase
Number of Poles	3
Current Rating	60 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 4/4X/5 stainless steel 304
Motor power hp	10 Hp at 240 V AC 50-60 Hz for 1 phase motors 20 Hp at 240 V AC 50-60 Hz for 3 phase motors 25 Hp at 480 V AC 50-60 Hz for 1 phase motors 50 Hp at 480 V AC 50-60 Hz for 3 phase motors 30 Hp at 600 V AC 50-60 Hz for 1 phase motors 60 Hp at 600 V AC 50-60 Hz for 3 phase motors 10 Hp at 250 V DC 30 hp at 600 V DC

### Complementary

Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	3-wire
Wire Size	AWG 14AWG 3 copper AWG 12AWG 3 aluminium
Tightening torque	50 Lbf.In (5.65 N.m) (AWG 3) 45 Lbf.In (5.08 N.m) (AWG 6AWG 4) 40 Lbf.In (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 50 lbf.in (5.65 N.m) 0.0001 in² (2.065.261 mm²) (AWG 14AWG 10)
Depth	6.97 in (177.04 mm)
Width	10.81 in (274.57 mm)
Height	16.87 in (428.50 mm)
Net Weight	19.84 lb(US) (9 kg)

#### Environment

	III listed file F2075
Certifications	UL listed file E2875
OCI IIIIOGIIO113	OL IISICA IIIC EZOTO

#### Ordering and shipping details

Category	00010-H&HU SW,2&3P,N4,SS,30-200A
Discount Schedule	DE1
GTIN	785901023685
Returnability	Yes
Country of origin	US

# Packing Units

Unit Type of Package 1	PCE
Office Type of Fackage 1	FOE
Number of Units in Package 1	1
Package 1 Height	9.50 in (24.13 cm)
Package 1 Width	14.50 in (36.83 cm)
Package 1 Length	19.70 in (50.038 cm)
Package 1 Weight	19.14 lb(US) (8.682 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	40
Package 2 Height	45.50 in (115.57 cm)
Package 2 Width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	766.00 lb(US) (347.451 kg)

# Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

#### Contractual warranty

Warranty	18 months