



**Note:**

- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:

**XCKM115H7**



Telemecanique Sensors  
 1875 Founders Drive  
 Dayton, OH 45420-4017  
 Customer Care Center : 1-800-435-2121  
 Web : www.tesensors.com

**Technical Information:**

Terminal Type: Screw Clamp  
 Enclosure Rating: NEMA 4/12; IP65  
 Approvals: UL # E39281 - CSA # LR44087 Class 3211-03 - CE Marked  
 Weight: 0.285 kg (0.628 lb)  
 Conforming to Standards:  
 RoHS: Yes  
 Operating Temperature Range: -13 to 158 ° F  
 Shock Resistance: 50G  
 Vibration Resistance: 25G (10-500Hz)  
 Max. Actuation Speed : 1.5 m/s  
 Repeat Accuracy:  
 Operating Torque/Force: 14.16 Inch-Ounces (0.10Nm)

**Specification:**

Description: XCKM Limit Switch Plastic roller lever  
 Body Style/Type Description: IEC OsiSense Limit Switches XCKM Compact SemiModular 64 mm Metal Body  
 Head Type: ZCKD05 Rotary, actuation from left and right + ZCKY15 thermoplastic roller lever  
 Lever Arms: ZCKY15 Thermoplastic roller lever  
 Body with Contact Type: ZCKM1H7 2-pole N.O./N.C. Snap Action  
 Conduit Thread: 3 entries CM10  
 Ampere Rating Continuous: 10A  
 Maximum Voltage Rating: 240VAC/250VDC  
 Actuation: CW and CCW  
 Actuator Action: Momentary  
 Lever Arm Length: 34.5mm  
 Roller Dimension: 0.63 x 0.21 in  
 Roller Material: Thermoplastic  
 Contact Configuration: 1 N.O./1 N.C.  
 Contact Operation: Snap Action  
 Connection Type: CM10 with #DE9RA1012 adapter for 0.5 Inch NPT  
 Head Material: Zamak  
 Positive Opening: Yes  
 Cable Length: