



Overview

| | |
|-----------|------------------------------|
| Lead time | Usually Ships within 4 Weeks |
|-----------|------------------------------|

Main

| | |
|---------------------------|--|
| Range | ClimaSys |
| Product name | ClimaSys CV |
| Product or Component Type | Fan |
| Type of filter | Standard |
| Flow rate | Free flow rate with standard filter: 79253.03 Gal/hr(US) (300 m ³ /h) at 50 Hz Free flow rate with standard filter: 92461.87 Gal/hr(US) (350 m ³ /h) at 60 Hz |
| [Us] rated supply voltage | 145...253 V |
| Input voltage | 230 V 50/60 Hz |

Complementary

| | |
|---------------------------------------|---|
| Absorbed power | 36 W 50 Hz 37 W 60 Hz |
| Line Rated Current | 0.16 A 60 Hz 0.17 A 50 Hz |
| Noise level < at | 55...56 dB |
| Bearing type | Ball |
| Height | External 10.55 in (268 mm) |
| Width | External 9.76 in (248 mm) |
| Depth | External 4.57 in (116 mm) |
| Cut-out dimensions | 223 x 223 mm |
| Net Weight | 2.87 lb(US) (1.3 kg) |
| Material | Outlet grille injected thermoplastic (ASA PC) |
| Color | Outlet grille Gray RAL 7035) |
| Ambient Air Temperature for Operation | 14...158 °F (-10...70 °C) |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Maximum pressure | 158 Pa flow rate 0 m ³ /h |
| Connections - Terminals | Faston connector |
| IP degree of protection | IP54 |

| | |
|--------------------|---|
| Device composition | 1 axial motor 2 protective grille on the front and rear surfaces 1 filter front of axial motor 1 outlet grille front 1 cut-out template 1 power cord |
| Condition of use | Surrounding environment must be relatively clean Filter must be cleaned and replaced regularly Outside temperature must be 5 °C lower than inside temperature Overfrequent filter replacement should be avoided Flow rates depends on the work point, see ProClima software |

Ordering and shipping details

| | |
|-------------------|-------------------------------------|
| Category | 80036-ENCLOSURE SYSTEMS ACCESSORIES |
| Discount Schedule | ES1 |
| GTIN | 3606480151286 |
| Returnability | No |
| Country of origin | FR |

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.28 in (18.5 cm) |
| Package 1 Width | 10.04 in (25.5 cm) |
| Package 1 Length | 10.63 in (27.0 cm) |
| Package 1 Weight | 3.62 lb(US) (1.642 kg) |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 4 |
| Package 2 Height | 11.02 in (28.0 cm) |
| Package 2 Width | 15.75 in (40.0 cm) |
| Package 2 Length | 23.62 in (60.0 cm) |
| Package 2 Weight | 16.48 lb(US) (7.476 kg) |
| Unit Type of Package 3 | P12 |
| Number of Units in Package 3 | 64 |
| Package 3 Height | 37.40 in (95.0 cm) |
| Package 3 Width | 31.50 in (80.0 cm) |
| Package 3 Length | 47.24 in (120.0 cm) |
| Package 3 Weight | 297.62 lb(US) (135.0 kg) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|