## VW3S8201R50

cable for pulse/direction signal, Lexium SD3, 5V, shielded, 5m



## Main Accessory / separate Cable for pulse/direction signal part designation Accessory / Separate Connecting cable Part Type Accessory / separate Connection accessories part category Accessory / separate Between stepper drive SD326 and external impulsion part destination generator Range Compatibility Lexium SD3 Type of Cable Shielded cable

16.40 ft (5 m)

Complementary

Product Compatibility	SD326
[Uc] control circuit voltage	5 V
Electrical connection	1 connector 24-pole Molex SD326) Cable end open external impulsion generator)

Cable length

Ordering and shipping details

Category	18286-STEPPER ACCESSORIES
Discount Schedule	PC55
GTIN	3389119224598
Returnability	No
Country of origin	CZ

**Packing Units** 

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.18 in (3.0 cm)
Package 1 Width	10.24 in (26.0 cm)
Package 1 Length	11.02 in (28.0 cm)
Package 1 Weight	16.37 oz (464.0 g)
Unit Type of Package 2	S06
Number of Units in Package 2	60
Package 2 Height	28.94 in (73.5 cm)
Package 2 Width	23.62 in (60.0 cm)
Package 2 Length	31.50 in (80.0 cm)
Package 2 Weight	90.04 lb(US) (40.84 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
PVC free	Yes

## Contractual warranty

ontractal warranty		
Warranty	18 months	