# QOUR240

application

Mini circuit breaker, QOU, 40A, 2 pole, 120/240 VAC, 10kA, field reversible lugs





Main	
Product or Component Type	Miniature circuit-breaker
Range of Product	QOU
Circuit breaker type	Standard
Circuit breaker	HACR rated

Complementary

Complementary		
Line Rated Current	40 A	
Electrical connection	Slotted box lugs, line side	
	Slotted box lugs, load side	
[Ue] rated operational voltage	120/240 V AC	
	120 V AC	
	48 V DC	
Mounting Mode	Unit mount	
AWG gauge	AWG 14AWG 2 aluminium/copper	
Height	4.05 in (102.87 mm)	
Width	1.5 in (38.10 mm)	
Depth	2.95 in (74.93 mm)	
Tightening torque	45 lbf.in (5.08 N.m) (AWG 14AWG 2)	

#### Environment

Product Certifications	IEC	
	UL Listed	
	CSA	

### Ordering and shipping details

Category	00900-QOU BREAKERS & SWITCH
Discount Schedule	DE2
GTIN	785901079347
Returnability	No
Country of origin	MX

### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.20 in (5.588 cm)	
Package 1 Width	3.70 in (9.398 cm)	
Package 1 Length	4.90 in (12.446 cm)	
Package 1 Weight	12.96 oz (367.41 g)	

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	<sup>™</sup> China RoHS Declaration	
RoHS exemption information	€Yes	
Halogen content performance	Halogen free product	

## Contractual warranty

Warranty	18 months