


Note:
 - Drawings Not To Scale
 - Drawings Subject to Change Without Notice
 - Dimensions are inches next to [Millimeters]

Part No.:

RE22R1MLMR



Schneider Electric United States
 North American Division
 Boston One Campus
 800 Federal Street
 Andover, MA 01810, USA
 Phone: +1 8773425173
 Email: CCC@us.schneider-electric.com

Technical Information:

Max. Switching Current:	8A
Max. Switching Voltage:	250 V
Max. Power Consumption:	3VA (AC), 1.5W (DC)
Input Signals	X1 – Pause Signal, X2 – Select Time Function, Z1,Z3- Ext Potentiometer
Function Available:	L, Li, Lt
Function Description:	Asymmetrical flashing relay
Time Ranges:	0.05 s to 300 h
Type of Output:	Relay
Contact Configuration:	SPDT

Specification:

Description:	Timer, 24-240 VAC/VDC Input, 8A SPDT Relay Output, Flashing
Ambient Storage Temp.:	-40 to +70 °C (-40 to +158 °F)
Ambient Operating Temp.:	-20 to +60 °C (-4 to +140 °F)
Degree of Protection Term. Block:	IP20
Degree of Protection Housing:	IP40
Electrical Life @ Rated Load:	100,000 cycles
Mechanical Life @ Rated Load:	20,000,000 cycles
Dial Settings:	Range = 1s to 300h, Ta = 1 to 10, Range = 1s to 300h, Tr = 1 to 10
Mounting:	35 mm DIN Rail